

RECEIVED

APR 19 1978

Auglaize County Engineer's Office
Clayton Stimmel, P.E.
County Engineer

Scale:

"A"

N. LINE ~ SEC. 2 & E. GEIGER

"B"

ROAD

2492.52'


N. 88° 46' 44" E. ~ 150.00'

11.99'

"E" N. 88° 46' 44" E.

S. 01° 16' E.
30.00'

LOCATION
SKETCH



SEC. 2


LEGEND
"A" = RAILROAD SPIKE @ S.W. COR. SEC. 35 NOBLE TWP.
"B" = STONE @ SOUTH 1/4 POSTN SEC. 35 NOBLE TWP.
"C" = 5/8" IRON BAR @ NORTH 1/4 POSTN SEC. 2 ~ ST. MARYS TWP.
"D" = CONC. POST FD. ON N ~ S 1/2 SEC. LINE ~ SEC. 2.
"E" = 5/8" IRON BAR SET.

1.406 ACRES

N. 01° 16' W. ~ 473.35'

S. 01° 16' E. ~ 343.20'

N ~ S 1/2 SECTION LINE



S. 47° 48' 44" W.
198.52'

"E"

50.00'

NORFOLK & WESTERN R.R.

S. 01° 16' E.
396.46'

"D"

SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR
No. 5372

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

GORDON L. GEESLIN

Client BARRY KEMP
County AUGLAIZE Twp. ST. MARYS Sec. 2
Drawn by GG Scale 1" = 60' Drwg. No. _____
Checked by GG Date 4-12-78
Sheet 1 of 2


379

SURVEYOR 5372

379

(T. 6 S.; R. 4 E.)

SURVEY DESCRIPTION



Scale: _____

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the northeast quarter of the northwest quarter of Section 2, Town 6 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a 5/8 inch iron bar at the north quarter post of said Section 2-

Thence, south 01°16' east along the north-south half section line of said Section 2, a distance of thirty (30.00) feet to a 5/8 inch iron bar in the south line of Geiger Road. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing south 01°16' east along the last described line, a distance of three hundred forty-three and 20/100 (343.20) feet to a 5/8 inch iron bar in the north right-of-way line of the Norfolk and Western Railroad-

Thence, south 47°48'44" west along said north right-of-way line, a distance of one hundred ninety-eight and 52/100 (198.52) feet to a 5/8 inch iron bar-

Thence, north 01°16' west, a distance of four hundred seventy-three and 35/100 (473.35) feet to a 5/8 inch iron bar in the afore mentioned south line of Geiger Road-

Thence, north 88°46'44" east along said south line of Geiger Road, a distance of one hundred fifty (150.00) feet to the place of beginning.

Containing 1.406 acre of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372 dated April, 1978, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Gordon L. Geeslin
Registered Surveyor
St. Marys, Ohio

Client BARRY KEMP
County AUGLAIZE Twp ST. MARYS Sec. 2
Drawn by _____ Scale As Shown Dwg. No. _____
Checked by _____ Date 4-12-78
Sheet 1 of 2 **380** (T 615 R 2 E)

380