

THIS SURVEY IS RECORDED AT THE AUGLAIZE COUNTY'S ENGINEERS OFFICE IN
BOOK "D" PAGE "138"




SR #219

FULL SECTION LINE

Scale:

1" = 20'

SECTION 26
WASHINGTON TWP



T-6 S-R 5 E

AUGLAIZE COUNTY

LEGEND

- R.R. SPIKE SET
- ✕ R.R. SPIKE FOUND
- I.P. SET

KETTLERSVILLE ROAD T-III

6" WOOD POST
21.3' FROM E

550.34' to E

89° 27'

90° 33'

3.935 Ac.

90° 33'

89° 27'

200'

550.34' to E

311.44'


EXIST. FARM BLOCS.

SECTION STONE

DUG FOR AND FOUND

RR. SPIKE PLACED OVER
STONE

1/2 SEC. LINE



Thomas W. Steinke

SOUTHLAND ROAD

FULL SEC. LINE

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____ Date _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

THOMAS W. STEINKE
Land Surveying

Client EARL KRITZER

County AUGLAIZE

Twp. WASHINGTON Sec. 26

Drawn by Hans S.

Scale 1" = 20' Drwg. No. 77 540

Checked by W. S.

Date Aug 17, 1978

Sheet _____ of _____

(T-6 S-R 5 E)



THOMAS W. STEINKE & ASSOC., INC.
LAND SURVEYING LAND DEVELOPMENT
106 PARK STREET WAPAKONETA, OHIO 45895
PHONE: 419-738-7421

Being 3.935 Acres located in the north-west quarter of Section 26, T-6-S, R-5-E, Washington Township, Auglaize County, Ohio and being further described as follows:

Commencing at a corner stone at the south-west corner of the north-west quarter of Section 26.

Thence north with the west line of Section 26 and the center of Kettlersville Road ^{T-111} a distance of 1476.71 feet to a railroad spike and the PLACE OF BEGINNING for the parcel herein described.

Thence continuing north with said center line and section line, a distance of 311.44 feet to a railroad spike.

Thence east with an interior angle of $89^{\circ} 27'$, a distance of 550.34 feet to an iron pipe, passing through a 6" wood post at 21.3 feet.

Thence south with an interior angle of $90^{\circ} 33'$, a distance of 311.44 feet to an iron pipe.

Thence west with an interior angle of $89^{\circ} 27'$, a distance of 550.34 feet to a railroad spike and PLACE OF BEGINNING, passing through an iron pipe at 530.34 feet.

Containing in all 3.935 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke and Assoc., Inc, this 17th day of August, 1978 and recorded in Survey Book "D" Page 138 of the Auglaize County Survey Records.