



Surveyors Description
for
Section 32

Scale: _____

The following tract of ground is part of the Southeast Quarter of the Northeast Quarter of Section 32, Goshen Township, Township Five(5) South, Range Eight(8) East, Auglaize County, Ohio and is more particularly described as follows:

The PLACE OF BEGINNING is an iron pin at the Southeast corner of the Northeast Quarter of Section 32, Goshen Township;

Thence N89°-06'W a distance of 441.66 feet to an iron pin in the centerline of an open ditch;

Thence N07°-21'-10"E with the centerline of an open ditch a distance of 288.32 feet to an iron pin;

Thence N78°-48'-15"W with the centerline of an open ditch a distance of 923.73 feet to a point;

Thence N01°-05'-20"E with the centerline of an open ditch a distance of 890.66 feet to an iron pin;

Thence S88°-33'-15"E a distance of 1350.30 feet to a point in the East line of Section 32;

Thence S02°-24'-40"W along said section line a distance of 1329.88 feet to an iron pin and the PLACE OF BEGINNING.

The above described tract of ground contains 33.34 Acres and is subject to all easements of record.

Surveyors Description
for
Section 33

The following described tract of ground is part of the West 1/2 of the West 1/2 of Section 33, Goshen Township, Township Five (5) South, Range Eight(8) East, Auglaize County, Ohio and is more particularly described as follows:

The PLACE OF BEGINNING is an iron pin at the Southwest corner of the Northwest Quarter of Section 33, Goshen Township;

Thence N02°-24'-40"E along said section line a distance of 1329.88 feet to a point;

Thence S88°-33'-15"E a distance of 62.70 feet to a 12" concrete endpost;

Thence S88°-56'-25"E a distance of 1194.59 feet to a nail in the centerline of State Route # 196(Sta. 43+62.61 of State R/W Plans);

Thence S10°-30'W along said centerline a distance of 511.67 feet to a nail at the PT of a curve;

Thence with a curve ($\Delta = 5^\circ-33'$, $D^\circ=1^\circ-30'$, $T=185.14'$, $L=370.00'$, $R=3819.72'$, $L.C.=369.87'$) having a Long Chord bearing of S07°-43'-30"W and length of 369.87 feet to a nail at the PC of the curve(Sta. 34+80.94 State R/W Plans);

Thence S04°-57'W along the centerline of State Route # 196 a distance of 2680.59 feet to a nail(Sta. 8+00.35 State R/W Plans);

Thence N88°-49'-15"W a distance of 341.09 feet to a 4" angle iron post;

Thence S03°-28'W a distance of 194.89 feet to a 4" angle iron post;

Thence N88°-50'W a distance of 687.47 feet to a 4" angle iron post;

Thence N02°-24'-40"E along the West line of Section 33 a distance of 2410.85 feet to an iron pin and the PLACE OF BEGINNING.

The above described tract of ground contains 94.08 Acres of which 2.45 Acres has been dedicated for highway purposes and is subject to all easements of record.

All bearings were based upon state right-of-way plans for S.R.# 196.

Total Acreage for Sections 32 & 33 equals 127.42 Acres.

Previous Deed Reference: Volume 179, 146
Page 227, 626

ATTEST: Douglas Reinhart
Douglas Reinhart
Professional Surveyor #6507

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.

Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.

Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____
for political S. D. of. _____ Date _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.

Signed: _____ Date _____

Client Paul F. Reinhart

County Auglaize Twp. Goshen Sec. 32 & 33

Drawn by _____ Scale _____ Drwg. No. 78-101

Checked by _____ Date 1-8-79

Sheet 2 of 2 (T 5 S; R 8 E)