


Scale:
1" = 400'



- ☒ P K NAIL SET
- ☐ IRON PIPE SET
- ☒ IRON PIPE FD.
- ☒ R.R. SPIKE FD.
- ☐ CO. MON. BOX

B - 90°28' 40"
C - 89°31' 20"
D - 90°28' 40"
E - 89°31' 20"



SURVEY CONDUCTED BY:
THOMAS W. STEINKE & ASSOC., INC.
23 W. AUGLAIZE ST. WAPAKONETA OHIO

Signed: _____ Date _____

Signed: _____ Date _____

Signed: _____ Date _____

Signed: _____ Date _____

Client RALPH BROWN
County AUGLAIZE Twp. DUCHOUQUET Sec. 19
Drawn by GARRY MCD. Scale 1 60 Drwg. No. 78-702
Checked by T.W.S. Date DEC. 8, 1978
Sheet 1 of 2 **245** (T 5 S; R 6 E)

245

245

DESCRIPTION OF 1.000 ACRE

Being 1.000 Acre located in the south-west quarter of Section 19, Town - 5 - S, Range - 6 - E, Duchouquet Township, Auglaize County, Ohio and being further described as follows:

Commencing at a monument box at the north-west corner of the south-west quarter of Section 19.

Thence east with the half section line and the center line of the Infirmary Road (C.R.# 166), a distance of 1030.76 feet to a P.K. nail and Shinner and the PLACE OF BEGINNING for the parcel herein described.

Thence continuing eastward with said half section line and center line, a distance of 208.71 feet to a P.K. nail and shinner.

Thence southward along the west line of Sherwood Forest Subdivision with an interior angle of $89^{\circ} 31' 20''$, a distance of 208.71 feet to an iron pipe, passing through an iron pipe at 30.00 feet.

Thence westward with an interior angle of $90^{\circ} 28' 40''$, a distance of 208.71 feet to an iron pipe.

Thence northward with an interior angle of $89^{\circ} 31' 20''$, a distance of 208.71 feet to a P.K. nail in the half section line and center line of Infirmary Road (C.R. # 166) and the PLACE OF BEGINNING, passing through an iron pipe at 178.71.

Containing in all 1.000 Acre and being subject to 0.14 Acre in road R/W.

Survey and description prepared by Thomas W. Steinke and Assoc., Inc. this 8th day of December, 1978 and recorded in Survey Book "D" Page 245

D-246