This survey is Recorded in Book D Page 259 of the Auglauze Co. Engs Off

e, angla suavav



Scale: ANIW Con of Section North line of Section 2 ["1100" 90° 33' 43,50.00' 90"33 40" 89°26'20" 00.000 FENCE LINE 90° 33'40° 90° 53' 40" 89° 26' 20" LEGEND LOCATION P.K. Nails Shinner (000 IRON PIPE MONUMENT BOX I Beam 44.4 Mouron Twp. Section 33 T-5-5-A-5-E Auglaize co.o

SEE REVISED SURVEY

SURVEY CONDUCTED BY: OTHORIAS W. STEINKE & ASSOC., INC. 123 WEST AUGLAIZE ST. WAPAKONETA, OHIO 45895

| Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: | Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed: Date |
|---|---|
| | |
| Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: | Signature by a representative of the Auginize County Regional Planning Commission denotes approval of this plat. Signed: Date |

Thomas W. Steinke & Assoc., Inc.
Land Surveying
123 West Auguste St.
Wapakoneta, Only 45895

| Client | Robert | Engle | enables of the second s | ing and the second second second | stronomonatement de llade |
|--------------|----------|---------|--|---|--------------------------------------|
| A 1100 | laize | Twp. Mo | ulton | Sec | TAT WILD |
| Drawn by G . | McDonald | Scalel | 97 300 100 100 100 100 100 100 100 100 100 | Nati North | ///////// |
| Checked by _ | T.Steink | |)ale113 | the state of the second for the same of the condition | H. Landson |
| Sheet | Olman | OF | \mathbf{O} | (T.5.5; | R. 2.E) |
| | | 60 | y | | SELECTIC LANGE TO SELECT |

D-259 -

DESCRIPTION OF 1.7.22 ACRES 样定世

Being 1.722 Acres located in the Northwest quarter of Section 17 Moulton Township, T-5-S-R-5-E Auglaize County Ohio and being further described as follows.

Commencing at the northwest corner of section 17 said corner also being the west line of said section and the centerline of Moulton Ft. Amanda Road (C.R. 91)

Thence in a southerly direction along said west line of section and said centerline a distance of 30.00 feet to an Auglaize County monument box. Monument box being located at the intersections of Kruse Road and Moulton Ft. Amanda Road.

Thence in a easterly direction with the centerline of Kruse Road (T.R. 150) and parallel to the north line of section 17 a distance of 1576.76 feet to a p.k. nail and shinner.

Thence in a southerly direction with an angle to the left of 89°26 20" a distance of 30.00 feet to an iron pipe, and the PLACE OF BEGINNING for the tract of land herein described

Thence continuing in a southerly direction with last described course a distance of 300.00 feet to a iron pipe.

Thence in a westerly direction with an interior angle of 90°33 40" a distance of 250.00 feet to a point.

Thence in a northerly direction with an interior angle of 89°26'20" a distance of 300.00 feet to a steel " I " beam corner post.

Thence in a easterly direction with an interior of 90°33 40" a distance. of 250.00 feet to a iron pipe and the PLACE OF BEGINNING for this parcel.

containing in all 1.722 Acres and being subject to any and all easements and right-of-way of record.

Survey and description is recorded in book D page 260 of the Auglaise County Engineers Office survey records.

Survey and description prepared by . Thomas W. Steinke and Assoc. Inc. 123 West Auglaize St. Wapakoneta, Ohio 45895, this 15th day of Feb. 1979.

SEE Rewsed Survey E-263



DESCRIPTION OF 1.7.22 ACRES 草井乙

Being 1.722 Acres located in the Northwest quarter of Section 17 Moulton Township, T-5-S-R-5-E Auglaize County Ohio and being further described as follows.

Commencing at the northwest corner of section 17 said corner also being the west line of said section and the centerline of Moulton Ft. Amanda Road (C.R. 91)

Thence in a southerly direction along said west line of section and said centerline a distance of 30.00 feet to an Auglaize County monument box Monument box being located at the intersections of Kruse Road and Moulton Ft. Amanda Road.

Thence in a easterly direction with the centerline of Kruse Road (T.R. 150) and parallel to the north line of section 17 a distance of 1826.76 feet to a p.k. nail and shinner

Thence in a southerly direction with an angle to the left of 89°26'20" a distance of 30.00 feet to an iron pipe and the PLACE OF BEGINNING for this parcel.

thence continuing in a southerly direction with last described course a distance of 300.00 feet to an iron pipe.

Thence in a westerly direction with an interior angle of 90°33 40 a distance of 250.00 feet to an iron pipe.

Thence in a northerly direction with an interior angle of 89°26'20" a distance of 300.00 feet to an iron pipe.

Thence in a easterly direction with an interior angle of 90°33 40° a distance of 250.00 feet to an iron pipe, and the PLACE OF BEGINNING for this tract.

The above described contains 1.722 Acres and being subject to any and all easements and right-of-way of record.

Survey and description recorded in book D page 261 of the Auglaize county engineers office survey records.

Survey and description prepared by: Thomas W. Steinke and Assoc. Inc. 123 West Auglaize St. Wapakoneta, Ohio this 15 th day of Feb. 1979

SEE REVISED SURVEY E-263

262

0.262

262

Being 1.724 Acres located in the Northwest quarter of Section 17 Moulton Township, T-5-S-R-5-E Auglaize County Ohio and being further described as follows.

Commencing at the northwest corner of section 17 said corner also being the west line of said section and the centerline of Moulton Ft. Amanda Road (C.R. 91)

Thence in a southerly direction along said west line of section and said centerline a distance of 30.00 feet to an Auglaize County monument box. Monument box being located at the intersections of Kruse Road and Moulton Ft. Amada Road.

Thence in a easterly direction with the centerline of Kruse Road (T.R. 150) and parallel to the north line of section 17 a distance of 2077.90 feet to a p.k. nail and shinner

Thence in a southerly direction with an angle to the left of 89°34° a distance of 30.00 feet to a steel "I" beam corner post and the PLACE OF BEGINNING for this parcel.

Thence continuing in a southerly direction with last described course a distance of 300.00 feet to an iron pipe.

Thence in a westerly direction with an interior angle of 90°26 a distant of 251.80 feet to an iron pipe.

Thence in a northerly direction with an interior angle of 89°26 20° a distance of 300.00 feet to an iron pipe.

Thence in a easterly direction with an interior angle of 90°33 40° a distance of 251.14 feet to a steel " I " beam corner post and the PLACE OF BEGINNING FOR This parcel

The above described contains 1.724 acres and being subject to any and all easements and right-of-way of record/

Description and survey prepared by: Thomas W. Steinke and Assoc. Inc. 123 West Auglaize St. Wapakoneta, Ohio, this 15 th day of Feb. 1979.

This survey and description is recorded in book D page 262 of the Auglaize County Engineers Office survey records.

SEE REVISED
SLAVEY E-263