

PLAT RECORDED IN SURVEY BOOK D, PAGE 272, AUGLAIZE CO.



ATTEST: Doug Reinhart P.S.# 6507
DOUG REINHART

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

272

DOUG REINHART
LAND SURVEYING

Client WILLARD BEERS
County AUGLAIZE Twp. GOSHEN Sec. 8
Drawn by JOHN JAWET Scale 1"=60' Drwg. No. 79-144
Checked by DR Date FEB. 21 1979
Sheet 1 of 2

272

(T. 6 S. R. 8 E)



Scale: _____

Surveyors Description

The following described tract of land is part of the Northwest Quarter of Section 8, Goshen Township, Town 6 South, Range 8 East, Auglaize County, Ohio, and is more particularly described as follows:

Commencing at a monument box in the Northeast Corner of the Northwest Quarter of Section 8, Goshen Township and in the centerline of Township Road 130 (formerly known as the Goshen Road):

Thence N.89°50'W. along the centerline of Township Road 130 and the North line of Section 8, Goshen Township, a distance of 412.19 feet to a P.K. Nail which is the PLACE OF BEGINNING;

Thence continuing N.89°50'W. along the centerline of Township Road 130 and the North line of Section 8, Goshen Township, a distance of 308.72 feet to a P.K. Nail;

Thence S.01°54'W. a distance of 187.70 feet to an iron pin;

Thence S.87°21'E. a distance of 48.45 feet to an iron pin;

Thence S.00°44'W. a distance of 86.05 feet to an iron pin;

Thence S.86°18'E. a distance of 93.94 feet to an iron pin;

Thence N.10°45'E. a distance of 52.98 feet to an iron pin;

Thence N.75°54'E. a distance of 171.70 feet to an iron pin;

Thence N.00°47'W. a distance of 187.24 feet to a P.K. Nail in the centerline of Township Road 130 and the North line of Section 8, Goshen Township, said P.K. Nail being the PLACE OF BEGINNING.

Containing 1.64 acres of which 0.11 acres has been dedicated for highway purposes. The above described tract of land is subject to all legal easements. Previous deed reference: Vol.205, Page 822.

ATTEST:

Doug Reinhart
Doug Reinhart

Reg. Surveyor #6507

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

DOUG REINHART
SURVEYING

273

Client Willard Beers
County Auglaize Twp. Goshen Sec. 8
Drawn by Janert Scale _____ Drwg. No. 79-144
Checked by D.P.R. Date 2-21-79
Sheet 2 of 2

273

(T 6 S R 8 E)