

Being part of the south-east quarter of Section 10, T-5-S, R-5-E. Moulton Township. Auglaize County. Ohio and being further described as follows:

Commencing at the intersection of the center line of Main Street Road and the south line of Section 10. (The following courses to the PLACE OF BEGINNING are following the center line of Main Street Road)

Thence North 12° 13° 40" West, 153.68 feet.

Thence North 08° 28' 40" West, 218.61 feet.

Thence North 02° 36° 40" West, 82.02 feet.

Thence North 09° 25° 20" East, 78.2 feet.

Thence North 25° 25! 20" East. 92.2 feet.

Thence North 35° 01° 20" East, 329.6 feet to a railroad spike

Thence North 35° 36' 20" East, 563.24 feet to the quarter section line.

Thence South 89° 47' 15" West along said quarter section line, (not being on the center line of Main Street Road) a distance of 395.94 feet to an iron pipe and PLACE OF BEGINNING for the parcel herein described.

Thence continuing South 89° 47° 15" West, a distance of 607.02 feet to an iron pipe.and the half section line of Section 10

Thence South 02° 26° West with said half section line, a distance of 25.03 feet to a point.

Thence North 89° 47' 15" East, a distance of 608.18 feet to an iron pipe.

Thence North 00° 12' 45" West, a distance of 25.00 feet to the PLACE OF BEGINNING.

Containing in all 0.349 Acres.

Survey and description prepared by Thomas W. Steinke and Assoc., Inc. this 8th day of March, 1979 and recorded in Survey Book D Page 282 of the Auglaize County Survey Records.

> Thomas W. Steinke & Assoc., Inc. Land Surveying 123 West Auglaize St. Wapakoneta, Ohio 45895

D-283

Being part of the south-east quarter of Section 10. T-5-S, R-5-E. Moulton Township, Auglaize County, Ohio and being further described as follows:

Commencing at the intersection of the center line of Main Street Road and the south line of Section 10.

(The following courses to the PLACE OF BEGINNING are following the center line of Main Street Road)

Thence North 12° 13' 40" West, 153.68 feet.

Thence North 08° 28' 40" West, 218.61 feet.

Thence North 02° 36' 40" West, 82.02 feet.

Thence North 09° 25° 20" East. 78.2 feet.

Thence North 25° 25! 20" East. 92.2 feet.

Thence North 35° 01° 20" East, 329.6 feet to a railroad spike and the PLACE OF BEGINNING for the parcel herein described.

Thence South 89° 30°20" West, a distance of 694.62 feet to an iron pipe, in the half section line of Section 10.

Thence North 02° 26' East with said half section line, a distance of 25.03 feet to an iron pipe.

Thence North 89° 30° 20" East, a distance of 711.57 feet to a P.K. nail in the center line of Main Street Road.

Thence South 35° 36' 20" West with said center line, a distance of 30.94 feet to the PLACE OF BEGINNING.

Containing in all 0.404 Acres and being subject to 0.02 Acre in road right-of-way.

Survey and description prepared by Thomas W. Steinke and Assoc., Inc. this 8th day of March, 1979 and recorded in Survey Book D. Page 282 of the Auglaize County Survey Records.

Thomas W. Steinke & Assoc., Inc., i.and Surveying
123 West Auglaize St.
Wapakoneta, Ohio 45895

D-284