

SURVEY DESCRIPTION

PARCEL "A"

Scale:

Being a parcel of land situated in the northeast quarter of the northeast quarter of Section 20, Township 5 South, Range 4 East. Being more particularly described as follows:

The place of beginning for the parcel to be conveyed by this instrument is a P.K. nail set over the corner stone at the northeast corner of said Section 20, said point also being the intersection of the center lines of Noble Road and State Route #116.

Thence, South 0°14'40" West, along the east line of the northeast quarter of the northeast quarter of Section 20 and the center line of State Route #116, a distance of two hundred sixty and 00/100 (260.00) feet to a railroad spike;

Thence, West, a distance of three hundred and 00/100 (300.00) feet to a 5/8" iron bar;

Thence, North 0°14'40" East, a distance of two hundred sixty and 00/100 (260.00) feet to a railroad spike on the north line of the northeast quarter of the northeast quarter of said Section 20 and the center line of Noble Road;

Thence, East, along the north line of the northeast quarter of the northeast quarter and the center line of Noble Road, a distance of three hundred and 00/100 (300.00) feet to the place of beginning.


Containing 1.7906 acres of land more or less of which 0.3168 acres is in road right-of-way.

Subject to all easements and right-of-way of record.

The north line of the northeast quarter of Section 20 was assumed to bear East-West. All other bearings were calculated from angles turned.

Reference is made to a survey of this area by Michael L. Weadock, Registered Surveyor #6199, dated April, 1978, on file in the County Engineer's Office.

Surveyed by Michael L. Weadock
Michael L. Weadock
Registered Surveyor #6199



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

MICHAEL L. WEADOCK
REG. SURVEYOR #6199

ST. MARYS 355

Client STEVE DABBELT
County AUGLAIZE Twp. NOBLE Sec. 20
Drawn by M.L.W. Scale _____ Drwg. No. _____
Checked by M.L.W. Date APR. 28, 1978
Sheet 2 of 7 355

SURVEY DESCRIPTION

PARCEL "B"

Being a parcel of land situated in the northeast quarter of the northeast quarter of Section 20, Township 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a P.K. nail set over the cornerstone at the northeast corner of said Section 20, said point also being the intersection of the centerlines of Noble Road and State Route #116;

Thence, South 0°14'40" West, along the east line of the northeast quarter of the northeast quarter of said Section 20 and the centerline of State Route #116, a distance of two hundred sixty and 00/100 (260.00) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument;

Thence, continuing South 0°14'40" West, along the last described line, a distance of two hundred sixty and 00/100 (260.00) feet to a railroad spike;

Thence, West, a distance of three hundred and 00/100 (300.00) feet to a 5/8" iron bar;

Thence, North 0°14'40" East, a distance of two hundred sixty and 00/100 (260.00) feet to a 5/8" iron bar;

Thence, East, a distance of three hundred and 00/100 (300.00) feet to the place of beginning.

Containing 1.7906 acres of land more or less of which 0.1791 acres is in road right-of-way.

Subject to all easements and right-of-way of record.

The north line of the northeast quarter of the Section 20 was assumed to bear East-West. All other bearings were calculated from angles turned.

Reference is made to a survey of this area by Michael L. Weadock, Registered Surveyor #6199, dated April, 1978, on file in the County Engineers Office.

Surveyed by Michael L. Weadock
Michael L. Weadock
Registered Surveyor #6199



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.

Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.

Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____

for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.

Signed: _____ Date: _____

MICHAEL L. WEADOCK
REG. SURVEYOR #6199
ST. MARYS OHIO

Client STEVE DABBELT
County AUGLAIZE Twp. NOBLE Sec. 20
Drawn by M.L.W. Scale — Drwg. No. —
Checked by M.L.W. Date APR 28, 1978
Sheet 3 of 7

356

356

SURVEY DESCRIPTION

PARCEL "C"

Being a parcel of land situated in the northeast quarter of the northeast quarter of Section 20, Township 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a P.K. nail set over the cornerstone at the northeast corner of said Section 20, said point also being the intersection of the centerlines of Noble Road and State Route #116;

Thence, South 0°14'40" West, along the east line of the northeast quarter of the northeast quarter of said Section 20 and the centerline of State Route #116, a distance of eight hundred eight and 65/100 (808.65) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument;

Thence, continuing South 0°14'40" West, along the last described line, a distance of two hundred sixty and 00/100 (260.00) feet to a railroad spike;

Thence, North 89°59'24" West, a distance of three hundred and 00/100 (300.00) feet to a 5/8" iron bar;

Thence, North 0°14'40" East, a distance of two hundred sixty and 00/100 (260.00) feet to a 5/8" iron bar;

Thence, South 89°59'24" East, a distance of three hundred and 00/100 (300.00) feet to the place of beginning.

Containing 1.7906 acres of land more or less of which 0.1791 acres is in road right-of-way.

Subject to all easements and right-of-way of record.

The north line of the northeast quarter of Section 20 was assumed to bear East-West. All other bearings were calculated from angles turned.

Reference is made to a survey of this area by Michael L. Weadock, Registered Surveyor #6199, dated April, 1978, on file in the County Engineers Office.

Survey by Michael L. Weadock
Michael L. Weadock
Registered Surveyor #6199



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: _____ Date _____	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: _____ Date _____
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date _____	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: _____ Date _____

MICHAEL L. WEADOCK REGISTERED SURVEYOR #6199 - ST. MARKS, OHIO	Client <u>STEVE DABBELT</u> County <u>AUGLAIZE</u> Twp. <u>NOBLE</u> Sec. <u>22</u> Drawn by <u>M.L.W.</u> Scale _____ Drwg. No. _____ Checked by <u>M.L.W.</u> Date <u>APRIL 28, 1978</u> Sheet <u>4</u> of <u>7</u>
--	---

357

357

(T 5 S; R 4 E)

SURVEY DESCRIPTION

PARCEL "D"

Being a parcel of land situated in the northeast quarter of the northeast quarter of Section 20, Township 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a P.K. nail set over the corner stone at the northeast corner of said Section 20, said point also being the intersection of the center lines of Noble Road and State Route #116.

Thence, South $0^{\circ}14'40''$ West, along the east line of the northeast quarter of the northeast quarter of said Section 20 and the center line of State Route #116, a distance of one thousand sixty-eight and 65/100 (1068.65) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument;

Thence, continuing South $0^{\circ}14'40''$ West, along the last described line, a distance of two hundred sixty and 00/100 (260.00) feet to a railroad spike. Said point being the southeast corner of the northeast quarter of the northeast quarter of said Section 20;

Thence, North $89^{\circ}59'24''$ West, along the south line of the northeast quarter of the northeast quarter of said Section 20, a distance of three hundred and 00/100 (300.00) feet to a 5/8" iron bar;

Thence, North $0^{\circ}14'40''$ East, a distance of two hundred sixty and 00/100 (260.00) feet to a 5/8" iron bar;

Thence, South $89^{\circ}59'24''$ East, a distance of three hundred and 00/100 (300.00) feet to the place of beginning.


Containing 1.7906 acres of land more or less of which 0.1791 acres is in road right-of-way.

Subject to all easements and right-of-way of record.

The north line of the northeast quarter of Section 20 was assumed to bear East-West. All other bearings were calculated from angles turned.

Reference is made to a survey of this area by Michael L. Weadock, Registered Surveyor #6199, dated April, 1978, on file in the County Engineer's Office.

Surveyed by Michael L. Weadock
Michael L. Weadock
Registered Surveyor #6199



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

MICHAEL L. WEADOCK
REG. SURVEYOR #6199
ST. MARYS, OHIO

Client STEVE DABBELT
County AUGLAIZE Twp. NOBLE Sec. 20
Drawn by M.L.W. Scale _____ Drwg. No. _____
Checked by M.L.W. Date APR. 28, 1978
Sheet 5 of 7 (T 5 S; R 4 E)

SURVEY DESCRIPTION

Scale:

PARCEL "E"

Being a parcel of land situated in the northeast quarter of the northeast quarter of Section 20, Township 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at a P.K. nail set over the corner stone at the northeast corner of said Section 20, said point also being the intersection of the center lines of Noble Road and State Route #116.

Thence, West, along the north line of the northeast quarter of said Section 20, and the center line of Noble Road a distance of three hundred and 00/100 (300.00) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument;

Thence, continuing West, along the last described line, a distance of one thousand twenty-nine and 93/100 (1029.93) feet to a railroad spike. Said point being the northwest corner of the northeast quarter of the northeast quarter of said Section 20;

Thence, South 0 15'04" West, along the west line of the northeast quarter of the northeast quarter of said Section 20, a distance of one thousand three hundred twenty-eight and 42/100 (1328.42) feet to a 5/8" iron bar. Said point being the southwest corner of the northeast quarter of the northeast quarter of said Section 20;

Thence, South 89 59'24" East, along the south line of the northeast quarter of the northeast quarter of said Section 20, a distance of one thousand thirty and 00/100 (1030.00) feet to a 5/8" iron bar;

Thence, North 0 14'40" East, a distance of five hundred twenty and 00/100 (520.00) feet to a 5/8" iron bar, said line passing thru a 5/8" iron bar at two hundred sixty and 00/100 (260.00) feet;

Thence, South 89 59'24" East, a distance of three hundred and 00/100 (300.00) feet to a railroad spike on the east line of the northeast quarter of the northeast quarter of said Section 20 and the center line of State Route #116;

Thence, North 0 14'40" East, along said east line of the northeast quarter of the northeast quarter of said Section 20 and the center line of State Route #116, a distance of two hundred eighty-eight and 65/100 (288.65) feet to a railroad spike;

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.

Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.

Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____

for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.

Signed: _____ Date _____

MICHAEL L. WEADOCK
REG SURVEYOR #6199

ST. MARYS, OHIO

D-359

Client STEVE DABBELT
County AUGLAIZE Twp. NOBLE Sec. 20
Drawn by _____ Scale _____ Drwg. No. _____
Checked by M.L.W. Date APR 28, 1978
Sheet 6 of 7

359

(T 5 S: R 4 E)



Thence, West, a distance of three hundred and 00/100 (300.00) feet to a 5/8" iron bar; Scale:

Thence, North 0 14'40" East, a distance of five hundred twenty and 00/100 (520.00) feet to the place of beginning, passing thru a 5/8" iron bar at two hundred sixty and 00/100 (260.00) feet.

Containing 33.401 acres of land more or less of which 0.672 acres is in road right-of-way.


Subject to all easements and right-of-way of record.

The north line of the northeast quarter of Section 20 was assumed to bear East-West. All other bearings were calculated from angles turned.

Reference is made to a survey of this area by Michael L. Weadock, Registered Surveyor #6199, dated April, 1978, on file in the County Engineer's Office.

Surveyed by

Michael L. Weadock
Michael L. Weadock
Registered Surveyor #6199



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.

Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.

Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____

for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.

Signed: _____ Date _____

MICHAEL L. WEADOCK
REG. SURVEYOR #6199
ST. MARYS, OHIO

Client STEVE DABBELT
County AUGLAIZE Twp. NOBLE Sec. 20
Drawn by M.L.W. Scale _____ Drwg. No. _____
Checked by M.L.W. Date APRIL 28, 1979
Sheet 7 of 7 **360** (T 5 S; R 4 E)