


# WUEBBENHORST SR. SURVEY

Scale: \_\_\_\_\_

SURVEY BOOK D  
PAGE 387

LOCATION




SECTION 15  
PUSHETA TWP.  
T-6-S-R-6-E  
AUGLAIZE CO. O.

LEGEND

- ✕ R.R. SPIKE FD.
- ✕ IRON PIN FOUND
- IRON PIPE

OPEN DITCH



**SURVEY CONDUCTED BY:**  
**THOMAS W. STEINKE & ASSOC., INC.**

123 WEST AUGLAIZE STREET WAPAKONETA O. 45895

Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of City with 3 mile limit juris-  
diction or Twp. Trustees or Village with zoning jurisdiction  
denotes approval of this plat. Signed: \_\_\_\_\_ Date: \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Thomas W. Steinke & Assoc., Inc.  
Land Surveying  
123 West Auglaize St.  
Wapakoneta, Ohio 45895

Client CARL WUEBBENHORST SR.  
County AUGLAIZE Twp. PUSHETA Sec. 15  
Drawn by G. McDONALD Scale 1"=100' Drwg. No. \_\_\_\_\_  
Checked by T. STEINKE Date APRIL 2 1979  
Sheet 1 of 2 **387** (T 6 S; R 6 E)

D-387

**387**

**387**

(T 6 S; R 6 E)

DESCRIPTION OF 1.828 ACRES

Being 1.828 Acres located in the northeast quarter of section 15 Pusheta Township T-6-S-R-4-E Auglaize County, Ohio, and being further described as follows.

Commencing at the northeast corner of section 15 Pusheta Township being the centerline intersections of Pusheta Road ( T-R 120 ) and Fryburg Road ( C-R 171 ), said corner being marked by a railroad spike.

Thence S  $01^{\circ} 00'$  W along the ~~west~~<sup>East</sup> line of said section and the centerline of Fryburg Road a distance of 1849.91 feet to a railroad spike and the PLACE OF BEGINNING for the parcel of land herein described.

Thence continuing S  $01^{\circ} 00'$  W along said centerline and section line a distance of 318.48 feet to a railroad spike.

Thence N  $88^{\circ} 25'$  W a distance of 250.00 feet to a point.

Thence N  $01^{\circ} 00'$  E a distance of 318.48 feet to an iron pin.

Thence S  $88^{\circ} 25'$  E a distance of 250.00 feet to a railroad spike in the centerline of Fryburg Road ( C-R 171 ) also being a point on the ~~west~~<sup>East</sup> line of section 15, also being the PLACE OF BEGINNING for this parcel.

Containing in all 1.828 Acres and being subject to any and all easements and Right-of-Way of record.

This survey is recorded in Book "D" page 387 of the Auglaize County Engineers Office.

Survey and description prepared by: Thomas W. Steinke and Assoc. Inc.  
123 West Auglaize Street Wapakoneta, Ohio, 45895 this 4th day of April 1979.