THE STREET IS RECORDED IN BOOK E PAGE 55 OF THE PUGLAIZE COUNTY ENGINEERS OFFICE THIS PARCEL OF 1.000 AC 15 TO BE TRANSFEREND TO THE OWNER OF THE LANDS. AdjACENT South 7 14 1001 439.95 100 (Not To Be Useo As AN INDIVIDUAL SITE) (NOW PARCEL) 364.85 70 LOCATION 1:000 RCRE Sam Sugrey Book D Pq 298 GERMONTWP. SECTION 2 1.000 ACRE Openies Willand T-7-5-R-4-E FUGLALE Co. MNGLES LEGEND 103.60 N. 8,9° 41' 20' B. 887 50" O BK MAIL VD. F.W. MAIL SET C. 56°02' D . 1787 09 ' O R.A. SPINE STATE HOW STATE E . 127 17' 40" F: 912 10" G-123:58 SECTION LINE NOTE: OPEN DITCH HAS PERMINATE EASENENT WHICH DEED IS NOLUMNEZOW PRGE 48 OF THE RUGLAVLE COUNTY RECORDERS OFFICE RVEY CONDUCTED MAS W. STEINKE & ASSOC. INC. 123 W. AUGLAIZE STREET WAPAKONETA, 0.45895 PH.738-7421 Signature by a representative of the County Health Dept, denotes compliance with Health Regulations. Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed:_ Signed: Signature by a representative of City with 3 mile limit juris-Signature by a representative of the County Engineer's Dept. diction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: denotes that this plat meets tax map plat requirements. for political S. D. of: .. MISRUT Thomas W. Steinkow Asaoc.. Inc.
Land Surveying
123 West Aught 25th
Wangkoneta, Ohio. 45895 Client __ County NUGLENZE TWP. GERMEN Sec. 2.

Drawn by G. MS DONALD Scale V-100' Drwg. No. 757.5%

Checked by T. GIEMKS Date NUME 25.78

Being 1.000 Acres located in the southwest quarter of section 2. German Township T-7-S-R-4-E Auglaize County, Ohio, and being further described as follows.

Commencing at the southwest corner of section 2 said point being marked by a P.K. nail, also being the centerline intersections of Lock Two Road (C-R 70) and Quelhorst Road (C-R 41).

Thence in a northerly direction along the centerline of Quelhorst Road and the west line of section 2 a distance of 181.50 feet to a railroad spike and the PLACE OF BEGINNING for the parcel herein described.

Thence continuing on said centerline and west line of said section a distance of 232.43 feet to a P.K. nail.

Thence in a easterly direction with an angle to the left of 88° 50 a a distance of 269.55 feet to a P.K. nail in the centerline of New Bremen New Knoxville Road (C-R 65-A).

Thence in a southwesterly direction with an interior angle of 56° 02° along the centerline of C-R 65-A a distance of 160.60 feet to a P.K. nail

Thence in a southwesterly direction with an interior angle of 178° 09° along said centerline a distance of 118.95 feet to a railroad spike.

Thence in a westerly direction with an interior angle of 127° 17' 40" a distance of 105.50 feet to a railroad spike in the centerline of Quelhorst Road and a point on the west line of said section, also being the PLACE OF BEGINNING for this parcel.

Containing in all 1.000 Acres and being subject to any and all easements and Right-of-Way of record.

This survey is recorded in Book E Page 55 the Auglaize County Engineers Office survey records.

Survey and description prepared by: Thomas W. Steinke and Assoc. Inc. 123 West Auglaize Street Wapakoneta, Ohio this 25th day of June 1979.

Commencing at the southwest corner of section 2 said point being marked by a P.K. Nail, also being the centerline intersections of Lock Two Road (C-R 7D) and Quelhorst Road (C-R 4D)

Thence in a northerly direction along the centerline of Quelhorst Road and the west line of section 2 a distance of 551.33 feet to a P.K. nail and the PLACE OF BEGINNING for the parcel of land hereon described.

Thence continuing on said centerline and west line of said section a distance of 108.25 feet to a P.K. nail, marking the northwest corner of this parcel.

Thence in a easterly direction with an angle to the left of 88° 50 a distance of 439.95 feet to a P.K. nail in the centerline of New Bremen New Knoxville Road (C-R 65-A).

Thence in a southwesterly direction with an interior angle of 56° 02' along the centerline of C-R. 65-A a distance of 130.50 feet to a P.K. Nail.

Thence in a westerly direction with an interior angle of 123° 58' a distance of 364.85 feet to a P.K. nail in the centerline of Quelhorst Road and a point on the west line of section 2, also being the PLACE OF BEGINNING for this parcel.

Containing in all 1.000 Acres and being subject to any and all easements and Right-of-Way of record.

This survey is recorded in Book E Page 55 of the Au glaize County Engineers Office survey records.

Survey and description prepared by: Thomas W. Steinke and Assoc. Inc. 123 West Auglaize Street Wapakoneta. Ohio this 25th day of June 1979.