

THIS SURVEY IS RECORDED IN BOOK D PAGE 75 OF THE AUGLAIZE COUNTY ENGINEERS OFF.

# HAESEKER SURVEY

Scale: 1" = 50'

BEARINGS ORIENTED TO  
MATCH STATE OF OHIO  
SURVEY

S 00° 17' 40" E ~ 39.98

S 82° 07' 53" E ~ 40.40

D.B. 210  
PG 804

- IRON PIN OR PIPE FOUND
- CONCRETE MONUMENT FOUND

S 00° 57' 50" W  
245.8

N 00° 57' 50" E  
144.0

N 89° 33' 20" E  
105.0

S 86° 36' 55" E  
184.02

0.916 Ac.

D.B. 221  
PG 413

THIS PARCEL NEED TO BE CORRECTED BY  
A REVISED BOUNDARY SURVEY. THIS RESPONS-  
IBILITY IS THAT OF ROLLY PION

280.85

S 89° 30' W

N 74° 28' 40" W  
5.75

77.57

S 02° 34' 40" W


21.5

55.54

S 01° 17' 20" W

34.9

- A: State of Ohio Survey
- B: Geeslin Survey
- C: Pion Survey



PION SURVEY DOES NOT CLOSE  
ORIGINAL CORNERS Fd.  
HELD ORIGINAL CORNERS



**SURVEY CONDUCTED BY :**  
**THOMAS W. STEINKE & ASSOC. INC.**

123 W. AUGLAIZE STREET WAPAKONETA, O. 45895 PH. 738-7421

Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of City with 3 mile limit juris-  
diction or Twp. Trustees or Village with zoning jurisdiction  
denotes approval of this plat. Signed: \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

75

Thomas W. Steinke & Assoc. Inc.  
Land Surveying  
123 West Auglaize St.  
Wapakoneta, Ohio 45895

Client LOUIS HAESEKER  
County AUGLAIZE Twp. ST. MARY'S Sec. FOUR  
Drawn by G. McDONALD Scale 1" = 50' Drwg. No. 72-797  
Checked by T. STEINKE Date MAY 16 1979  
Sheet 1 of 2

75

(T 6 S; R 4 E)

Being 0.916 Acres located in the south-west quarter of Section 4, T-6-S, R-4-E, St. Marys Township, Auglaize County, Ohio and being further described as follows. Commencing at the intersection of the center line of S.E.# 703 and the west line of Section 4.

Thence S  $00^{\circ} 17' 40''$  E with said section line, a distance of 39.98 feet.

Thence South  $82^{\circ} 07' 53''$  East, a distance of 40.40 feet. to the east R/W line of S.R.# 364.

Thence South  $00^{\circ} 57' 50''$  West along said center line, a distance of 245.8 feet to an iron pin found, and the PLACE OF BEGINNING for the parcel herein described.

Thence North  $89^{\circ} 33' 20''$  East, a distance of 105.0 feet to an iron pin found.

Thence South  $86^{\circ} 36' 55''$  East, a distance of 184.02 feet to an iron pin found.

Thence South  $02^{\circ} 34' 40''$  West, a distance of 77.57 feet to an iron pin found.

Thence North  $74^{\circ} 28' 40''$  West, a distance of 5.75 feet to an iron pin found.-

Thence South  $01^{\circ} 17' 20''$  West, a distance of 55.54 feet to an iron pin found.

Thence South  $89^{\circ} 30'$  West, a distance of 280.85 feet to a concrete monument.

Thence North  $00^{\circ} 57' 50''$  East, a distance of 144.0 feet to the PLACE OF BEGINNING.

The purpose of this description is to transfer all of the lands now owned and occupied by Louis C. and Nina Haeseker as described in Deed Book 221 Page 413 except that portion of 0.620 Acres already survey off By Gordon Geeslin Dated December, 1978. The foregoing description describes the lands as monumented upon the ground. Errors exist in the Survey performed by Mr. Rollie Pion and must be corrected.

E-76