


THIS PLAT IS REQUIRED BY SECTION 17427 96 OF THE HUGLAIZE COUNTY ENGINEERS OFFICE



Scale:

SECTION



NOBLE TWP.
SECTION 30
T. 5. S. R. 4. E.
HUGLAIZE CO. O.

WE COR.
N/W 1/4

CLYNNWOOD RD
N. LINE OF SECTION

(25)

308.90' TO C

298.90' TO C

1.50 ACRES

(25)

170.00'

(25)

170.00'

- LEGEND
- X IRON PIPE FD.
 - O IRON PIPE SET
 - X RR. SPIKE FD.
 - O RR. SPIKE SET
 - B CO. MONUMENT SET

- ANGLES
- A = 90° 08' 20"
 - B = 89° 51' 40"
 - C = 90° 08' 20"
 - D = 89° 51' 40"

STILL

SURVEY CONDUCTED BY :
THE STEVENS & ASSOC. INC.

103 W. AUGLANT ST. APN. STA. 0.46895 PH. 738-7421

Signature by a person authorized to execute this plat.
Denotes compliance with the requirements of the
Signed _____ Date _____

Signature by a representative of the Auglaize County Regional
Finance Commission. Denotes approval of this plat.
Signed _____ Date _____

Signature by a representative of the County Engineer's Dept.
Denotes approval of this plat.
Signed _____ Date _____

Signature by a representative of the County Engineer's Dept.
Denotes approval of this plat.
Signed _____ Date _____

96

96

DESCRIPTION OF 1.250 ACRES

Being 1.250 Acres located in the west half of section 30. T-5-S-R-4-E Noble Township, Auglaize County, Ohio and being further described as follows.

Commencing at the northeast corner of the northwest quarter of section 30 said corner being marked by a Auglaize county monument box, also being the centerline intersections of Koenig Road (T-R 15) and Glynwood Road (T-R 1

Thence in a southerly direction along the centerline of Koenig Road , and and the north/south half section line a distance of 1607.50 feet to a railroad spike and the PLACE OF BEGINNING for the parcel of land herein described.

Thence continuing on said half section line and centerline of Koenig Road in a southerly direction a distance of 178.00 feet to a railroad spike, marking the southeast corner of this parcel.

Thence in a westerly direction with a angle to the left of $90^{\circ} 08' 20''$ a distance of 305.90 feet to a point, passing through a iron pipe at 25.00 feet.

Thence in a northerly direction with an interior angle of $89^{\circ} 51' 40''$ a distance of 178.00 feet to a iron pipe, marking the northwest corner of this parcel.

Thence in a easterly direction with an interior angle of $90^{\circ} 08' 20''$ a distance of 305.90 feet to a railroad spike in the centerline of Koenig Road and a point on the north/south half section line, also being the PLACE OF BEGINNING for this parcel, passing through a iron pipe at 280.90 feet.

Containing in all 1.250 Acres and being subject to any and all easements and Right-of-Way of record.

This survey is recorded in Book E Page 96 of the Auglaize County Engineer's Office survey records.

Survey and description prepared by: Thomas W. Steinke and Assoc. Inc.
123 West Auglaize Street Wapakoneta, Ohio this 6th day of August 1979.