

# PIEHL SURVEY

Scale:

STATE OF OHIO  
SEC. COR. REF.

STATE ROUTE 219  
PREVIOUSLY  
ESTABLISHED BY  
SURVEY & STATE  
OF OHIO

NORTH LINE OF SECTION 7  
S88°19'W 1328.31'

20.063 Ac.

N 88° 05' 30" E 1321.14'  
S 88° 05' 30" W 1321.14'

30.000 Ac.


N 88° 05' 30" E 1325.40'  
S 88° 05' 30" W 1325.40'

30.000 Ac.

N 01° 11' W 208.0'  
S 88° 49' W 208.0'

1329.78'  
N 88° 05' 30" E

LOCATION




WASHINGTON Twp  
SEC. 25 W 1/2  
T-6-S-R-5-E  
AUG. CO. O.

LEGEND

- ✱ P. K. NAIL
- AUG. CO. Mon. Box
- IRON PIPE
- R.R. SPIKE

CENTER OF SEC. ALSO  
SEC COR NW 1/4



*Thomas W. Steinke*



**SURVEY CONDUCTED BY :**  
**THOMAS W. STEINKE & ASSOC. INC.**

123 W. AUGLAIZE STREET WAPAKONETA, O. 45895 PH. 738-7421

Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of City with 3 mile limit juris-  
diction or Twp. Trustees or Village with zoning jurisdiction  
denotes approval of this plat. Signed: \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_ Date: \_\_\_\_\_

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date: \_\_\_\_\_

Thomas W. Steinke & Assoc., Inc.  
Land Surveying  
123 West Auglaize St.  
Wapakoneta, Ohio 45895

Client WOODY PIEHL  
County AUGLAIZE Twp. WASHINGTON Sec. 25  
Drawn by G. McDONALD Scale 1" = 400' Drwg. No. 79-860  
Checked by T. STEINKE Date 9/17/79  
Sheet 1 of 2

(T-6 S; R-5 E)

Being 30.000 Acres located on the north-west quarter of Section 25, Town 6-S, Range 5-E, Washington Township, Auglaize County, Ohio and being further described as follows:

Commencing at the south-east corner of the north-west quarter of Section 25, said point being marked by a monument box and the PLACE OF BEGINNING for the parcel herein described.

Thence North  $01^{\circ} 11'$  West with the north-south half Section line of Section 25 and the center line of Kohler Road T.R.# 125, a distance of 567.0 feet.

Thence South  $88^{\circ} 49'$  West, a distance of 208.0 feet.

Thence North  $01^{\circ} 11'$  West, a distance of 208.0 feet.

Thence North  $88^{\circ} 49'$  East, a distance of 208.0 feet to the center line of T.R.# 125.

Thence North  $01^{\circ} 11'$  West, a distance of 242.0 feet to a railroad spike.

Thence South  $88^{\circ} 05' 30''$  West, a distance of 1325.40 feet to an iron pipe.

Thence South  $00^{\circ} 56' 10''$  East, a distance of 1017.10 feet to an iron pipe in the east-west half section line of Section 25.

Thence North  $88^{\circ} 05' 30''$  East, with said half section line a distance of 1329.78 feet to the PLACE OF BEGINNING.

Containing in all 30.000 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke and Asso., Inc. this 17th day of September, 1979 and recorded in Survey Book E Page 113 of the Auglaize County Survey Records.

Being 20.063 Acres located in the north-west quarter of Section 25, Town 6-South, Range 5-East, Washington Township, Auglaize County, Ohio and being further described as follows:

Commencing at the north-east corner of the north-west quarter of Section 25, said point being marked by a State of Ohio P.K. Nail and the PLACE OF BEGINNING for the parcel herein described.

Thence South  $88^{\circ} 19'$  West along the center line of State Routh # 219 and the north line of Section 25, a distance of 1318.31 feet to a P.K. nail.

Thence South  $00^{\circ} 56' 10''$  East, a distance of 664.89 feet to an iron pipe.

Thence North  $88^{\circ} 05' 30''$  East, a distance of 1321.14 feet to a Railroad spike in the north-south half section line of Section 25 and the center line of Kohler Road T.R.# 125, also being 2004.64 feet north of the south-east corner of north-west quarter of Section 25.

Thence North  $01^{\circ} 11'$  West, a distance of 659.70 feet to the PLACE OF BEGINNING.

Containing in all 20.063 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke and Assoc., Inc. this 17th day of September, 1979 and recorded in Survey Book E Page 113 of the Auglaize Cpunty Survey Records.

Being 30.000 Acres located in the north-west quarter of Section 25, Town 6-S, Range 5-E, Washington Township, Auglaize County, Ohio and being further described as follows:

Commencing at the south-east corner of the north-west quarter of Section 25.

Thence North  $01^{\circ} 11'$  West, along the north-south half section line of Section 25 and the center line of Kohler Road T.R.# 125, a distance of 1017.0 feet to a railroad spike and PLACE OF BEGINNING for the parcel herein described.

Thence continuing North  $01^{\circ} 11'$  West with said center line and half section line, a distance of 987.64 feet to a railroad spike.

Thence South  $88^{\circ} 05' 30''$  West, a distance of 1321.14 feet to an iron pipe.

Thence South  $00^{\circ} 56' 10''$  East, a distance of 987.71 feet to an iron pipe.

Thence North  $88^{\circ} 05' 30''$  East, a distance of 1325.40 feet to a railroad spike and the PLACE OF BEGINNING.

Containing in all 30.000 Acres and being subject to all legal easements and R/W of record.

Survey and description prepared by Thomas W. Steinke and Assoc., Inc. this 17th day of September, 1979 and recorded in Survey Book E Page 113 of the Auglaize County Survey Records.