

L = 2996.35'
T = 1500.62'
Δ = 7°59'25" LT.
D = 0°16'
R = 21485.93'

1/2 SECTION LINE

N.E. CORNER,
SE 1/4, SECTION
34, NOBLE
TOWNSHIP


MON. F.D. 6 PT. STA. 249+85.33
MON. F.D. 6 STA. 255+00

E.S.R. 33 SURVEY

DISTANCE FROM E
TO TANGENT IS
0.39'

LOCATION PLAN

SECTION 34



NOBLE TOWNSHIP
T-5-S, R-4-E
AUGLAIZE COUNTY

TANGENT BEARING
N. 88°56'45" W.

LEGEND

- IRON PIN SET
- MONUMENT BOX
- P.K. NAIL FOUND
- P.K. NAIL SET

SURVEY I "CORRECT"
SEE 232

F. & L. FORTMAN
16.162 ACRES
0.751 AC. R/W

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

STATE ROUTE 66

ATTEST: Doug Reinhart
DOUG REINHART
REG. SURVEYOR NO 6507

S.E. CORNER,
SECTION 34,
NOBLE TWP

SEE TO SEC 38
ST. MARV 57 W

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____ Date _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

DOUG REINHART
LAND SURVEYING

Client BOB KUCK - FORTMAN
County AUGLAIZE Twp NOBLE Sec 34
Drawn by DOUG REINHART Scale 1"=200' Draw No 77-105
Checked by DDR Date Nov 18, 1979
Sheet 1 of 2 (T-5 S-R-4-E)

SURVEYORS DESCRIPTION
for
KUCK PROPERTY



Scale: _____

The following described tract of ground is part of the Southeast Quarter of Section 34, Noble Township, Township Five (5) South, Range Four (4) East, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box at the Southeast corner of Section 34, Noble Township; Thence N01°-30'-55"E along the East line of section 34 a distance of 719.19 feet to an iron pin and the PLACE OF BEGINNING;

Thence continuing N01°-30'-55"E along the East line of Section 34 a distance of 268.20 feet to an iron pin in the south right-of-way line of State Route # 33;

Thence S73°-18'-55"W along said right-of-way line a distance of 215.29 feet to an iron pin;

Thence S56°-41'-29"W along said right-of-way line a distance of 355.99 feet to an iron pin;

Thence S88°-51'-05"E parallel to the South line of section 34 a distance of 499.65 feet to an iron pin and the PLACE OF BEGINNING.

The above described tract of ground contains 1.794 Acres and is subject to all easements of record. Previous deed reference; Volume 202, Page 657, Auglaize County Recorders Office. Survey filed in Plat Book E, Page 168, Auglaize County Engineers Office. All bearings based on the centerline survey of State Route # 33 made by the Ohio Department of Transportation.

SURVEYORS DESCRIPTION
for
FORTMAN PROPERTY

The following described tract of ground is part of the Southeast Quarter of Section 34, Noble Township, Township Five (5) South, Range Four (4) East, Auglaize County, Ohio and is more particularly described as follows:

The PLACE OF BEGINNING is a monument box at the Southeast corner of Section 34, Noble Township; Thence N88°-51'-05"W along the south line of Section 34 and the centerline of Township Road # 140 (T.R. # 140 formerly known as McKinley Rd.) a distance of 1257.75 feet to a P.K. Nail;

Thence N01°-08'-55"E through an iron pin at 26.00 feet in the north right-of-way line of T.R. # 140 for a total distance of 35.00 feet to an iron pin in the right-of-way line of the S.R. 33 and S.R. 66 interchange;

Thence N10°-56'-50"E along said right-of-way line a distance of 185.05 feet to an iron pin;

Thence N56°-41'-29"E along said right-of-way line a distance of 386.85 feet to an iron pin;

Thence S88°-51'-05"E parallel to the south line of Section 34 a distance of 499.65 feet to an iron pin in the East line of Section 34;

Thence S01°-30'-55"W along the east line of Section 34 a distance of 719.19 feet to a monument box at the Southeast corner of Section 34 and the PLACE OF BEGINNING.

The above described tract of ground contains 16.162 Acres of which 0.751 Acres has been dedicated for highway use. The above described tract of ground is subject to all easements of record. Previous deed reference; Volume 241, Page 443, Auglaize County Recorders Office. Survey filed in Plat Book E, Page 168, Auglaize County Engineers Office. All bearings were based upon centerline survey of State Route # 33.

Attest: Doug Reinhart P.S.#6507

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Reinhart Surveying
Doug Reinhart, P.E., P.S.
R.R. # 6, Wapakoneta
Ohio 45895 Ph. 738-6755

Client Bob Kuck---Fortman
County Auglaize Twp. Noble Sec. 34
Drawn by _____ Scale _____ Drwg. No. 79-185
Checked by _____ Date Nov. 23, 1979
Sheet 2 of 2 (T 5 S; R 4 E)