

THIS SURVEY IS RECORDED IN BOOK E PAGE 225 OF THE AUGLAIZE COUNTY ENG'S OFF.


EAST-WEST HALF SECTION

KOHLER SURVEY

Scale:
1" = 100'

- LEGEND**
- X R.R. SPIKE FD.
 - ~ P.K. NAIL FD.
 - ~ P.K. NAIL SET
 - O IRON PIPE

LOCATION




PUSHETA TWP
SECTION 26
T. 6 S. R. 6 E
AUGLAIZE CO. O.

AREA

10.60 ACRES

WOODED



Thomas W. Steinke

WINEMILLER ROAD

735.24' TO E

S/E COR.
OF SEC.

SOUTHLAND ROAD T.R. 90
SOUTH LINE OF SECTION

633.50'

S/W COR.
S/E 1/4



SURVEY CONDUCTED BY:
THOMAS W. STEINKE AND ASSOCIATES INC.
123 WEST AUGLAIZE STREET WAPAKONETA, OHIO 45895

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: _____ Date: _____

Thomas W. Steinke & Assoc., Inc.
Land Surveying
123 West Auglaize St.
Wapakoneta, Ohio 45895

Client ED KOHLER
County AUGLAIZE Twp. PUSHETA Sec. 26
Drawn by G. McDONALD E.D. Scale 1" = 100' Drwg. No. 80932
Checked by T. STEINKE R.S. Date 2-19-80
Sheet 1 of 2 (T 6 S; R 6 E)

225

225



THOMAS W. STEINKE & ASSOC., INC.

LAND SURVEYING

LAND DEVELOPMENT

123 W. AUGLAIZE ST. - WAPAKONETA, OHIO 45895

PHONE: 419-738-7421

DESCRIPTION OF 10.60 ACRES

Being 10.60 Acres located in the east half of Section 26 Pusheta Township T-6-S-R-6-E Auglaize County Ohio, and being further described as follows.

Commencing at the south/west corner of the south/east quarter of section 26 Pusheta Township, said corner being marked by a railroad spike, also being the centerline intersection of Sidney Fryburg Road (T-R 73) and Southland Road (T-R 90), also being the PLACE OF BEGINNING for the parcel of land herein described.

Thence in a northerly direction along the centerline of Sidney Fryburg Road (T-R 73) and the north/south half section line a distance of 735.24 Feet (Seven hundred and thirty five feet and twenty four hundreds) to a P.K. Nail marking the north/west corner of this parcel.

Thence in a easterly direction with an angle to the left, being an interior angle to this parcel of $90^{\circ} 42' 40''$ a distance of 622.34 (Six hundred and twenty two feet and thirty four hundreds) to a iron pipe.

Thence in a southerly direction with an interior angle of $90^{\circ} 09' 20''$ a distance of 735.24 feet (Seven hundred and thirty five feet and twenty four hundreds) to a P.K. nail in the centerline of Southland Road (T-R 90) and being a point on the south line of section 26, Pusheta Township.

Thence in a westerly direction along the centerline of Southland Road (T-R 90) and along the south line of section 26 Pusheta Township with an interior angle of $89^{\circ} 49' 40''$ a distance of 633.50 feet (Six hundred and thirty three feet and five tenths) to a railroad spike, at the intersection of Southland Road (T-R 90) and Sidney Fryburg Road (T-R 73) said spike marking the south/west corner of the south/east quarter of section 26 Pusheta Township, also being the PLACE OF BEGINNING for this parcel.

Containing in all 10.60 Acres and Being subject to any and all easements and Right-of-Way of record.

This survey is recorded in Book E Page 225 Page of the Auglaize Co. Eng. office

Survey and description prepared by Thomas W. Steinke and Assoc. Inc.
123 West Auglaize Street Wapakoneta, Ohio this 19th day of Feb. 1980.