



Thomas W. Steinke & Assoc. Inc.
LAND SURVEYORS - LAND CONSULTANTS
123 W. AUGLAIZE ST. - WAPAKONETA, OHIO



BREWER SURVEY

N/E COR.
N/W 1/4

NORTH LINE OF SECTION



S 86° 50' 40" E
745.53

3.83 ACRES


N 01° 38' W
250.0'

7.39.95'
S 89° 19' W

DEED 277.55'
ACRUAL 277.48'
T.R. 15 500945'E

RIGHT-OF-WAY
200.0'
500945'E
KONNIG RD

LOCATION



NOBLE TWP.
SEC. 30 W 1/2
T-5-S-R-4E
AUGLAIZE Co. O.

LEGEND

- X IRON PIPE FD.
- O IRON PIPE SET
- X R.R. SPIKE FD.
- O R.R. SPIKE SET
- AUGLAIZE Co. Mon. Box

80-963

This survey is recorded in Book E Page 252 of the Auglaize Co. Engs. Office

TOWN 5 SOUTH RANGE 4 EAST

SCALE: 1" = 100'

AUGLAIZE COUNTY HEALTH DEPT.

AUGLAIZE COUNTY PLANNING COMM.

signature

date

signature

date

JURISDICTION 3 MILE LIMIT OR
TOWNSHIP

AUGLAIZE COUNTY ENGINEER

signature

date

signature

date

CLIENT: BREWER

DATE: MAY 14, 1980

COUNTY: AUGLAIZE

TOWNSHIP: NOBLE

SECTION: 30 W 1/2

E 252

252

252



THOMAS W. STEINKE & ASSOC., INC.
LAND SURVEYING LAND DEVELOPMENT
123 W. AUGLAIZE ST. - WAPAKONETA, OHIO 45895
PHONE: 419-738-7421

DESCRIPTION OF 3.83 ACRES

Being 3.83 Acres located in the west half of Section thirty Noble Township T-5-S--R-4-E , Auglaize County, Ohio and being further described.

Commencing at the north/east corner of the north/west quarter of Section 30 Noble Township Auglaize County, Ohio, said corner being marked by a Auglaize County Monument Box, also being the intersection of Koenig Road (T-R 15) and the north line of said section.

Thence S $00^{\circ} 45'$ E along the centerline of Koenig Road (T-R 15) and the north/south half section line a distance of 277.48 feet to a railroad spike and the PLACE OF BEGINNING for the parcel of land herein described.

Thence continuing along said centerline and half section line a distance of 200.0 feet to a railroad spike.

Thence S $89^{\circ} 19'$ W a distance of 739.95 feet to a iron pipe marking the south/west corner of this parcel, passing through a iron pipe at 25.0 feet.

Thence N $01^{\circ} 38'$ W a distance of 250.0 feet to a iron pipe.

Thence S $86^{\circ} 50' 40''$ E a distance of 745.53 feet to a railroad spike in the centerline of Koenig Road, also being a point on the north/south half section line of said section, passing through a iron pipe at 720.47 feet, said railroad spike also being the PLACE OF BEGINNING for this parcel.

Containing in all 3.83 Acres and being subject to any and all easements and Right-of-Way of record.

This survey is recorded in Book E Page 252 of the Auglaize County Engineers Office survey records.

Survey and description prepared by Thomas W. Steinke and Assoc. Inc.
123 West Auglaize Street Wapakoneta Ohio this 14th day of May 1980.

File No. 80-963