

WILLIAM LINK SURVEY 48.76 ACRE PARCEL IN SECTION 5, LOGAN TOWNSHIP, TSS, RSE, Auglaize Co

Scale: The following described parcel of ground is part of the East half of Section 5, Logan Township, Township Five (5) South, Range Five (5) East, Auglaize County, Ohio and is more particularly decribed as follows:

Commencing at a monument box at the Southeast corner of Section 5. Logan Township: Thence N88 -00'W along the south line of Section 5 a distance of 570.96 feet to a spike in the centerline of Township Road # 89 (T.R. # 89 known as the Mitchell Road) and the PLACE OF BEGINNING;

Thence continuing N88 -00'W along the south line of Section 5 a

distance of 553,19 feet to an iron pin; Thence NO2 -17'-30"E a distance of -17'-30"E a distance of 2430.83 feet to a P.K. Nail in %

the centerline of State Route # 197;
Thence S76 -08'E along the centerline of State Route # 197 a distance of 841.24 feet to a P.K. Nail;

Thence \$35%-00%-40%E a distance of 487.33 feet to an iron pin in the centerline of County Road # 91 (C.R. # 91 formerly known as the Moulton Ft. Amanda Road) and the East line of Section 5;

Thence SO2 -09'W along the centerline of C.R. # 91 and the East line

Section 5 a distance of 912.84 feet to a spike;

Thence \$54°-34'W a distance of 185.91 feet to an iron pin; Thence \$65°-41'W a distance of 300.30 feet to an iron pin;

Thence S31 -17'W a distance of 61.42 feet to an iron pin; Thence S23 -34'E a distance of 1.31 feet to an iron pin; Thence N88 -00'W a distance of 26.76 feet to an iron pin;

Thence \$26 -01'-30"W a distance of 263.50 feet to an iron pin;

Thence SO3 -32'-30"W a distance of 149.35 feet to an iron pin;

Thence \$27 -03'-30"E a distance of 53.34 feet to an iron pin;

Thence S52 -12'-20"E a distance of 120.31 feet to a spike in the centerline of Township Road # 89;

Thence \$39°-00'-30"W a distance of 185.32 feet along the centerline 🙊 of T.R. # 89 to a spike and the PLACE OF BEGINNING.

The above described tract of ground contains 48.76 Acres of which 1.19 Acres has been dedicated for highway purposes. Previous deed references: Volume 141, Page 136 and Volume 211, Page 216, Auglaize County Recorders Office. Survey filed in plat Book E, Page 303, Auglaize County Engineers Office. All bearings based upon the centerline survey by the Ohio Department of Transportation of State Route # 197. Original corner monuments were found on the adjacent parcels as described in Volume 155. Page 522, of the recorders office. The bearings and dimensions given above are the actual field dimensions due to the error in the previous survey of the said adjacent parcel.

DOT CONTRACTOR OF CONTRACTOR O REINHART

REG. SURVEYOR

ATTEST:

Checked by

Sheet__

Doug Reinhart

Professional Surveyor # 6507

Date 6-8-80

 $(T_5, S; R_5, E)$

Signature by a representative of the County Health Dept. denotes compliance with itelliar fogulations. Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: for political S. D. of: Date		Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed:
		Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date
DOUGLAS P. REINHART 6507	Client County <u>Au</u> Drawn by	Bill Link glaize Twp. Logan Sec. 5 Scale Drwg. No. 80-191