FOILT OVER STAKE FOUND BY O.D.C	
STA. 92478 ON & STATE ROUTE!	196.
	W SE
88	S
NAW Over STONE FOUND BY OD.O AT STA. 79+47.80 ON & STATE F	SECTION PLAN SECTION 8 STEE SIJE
000 000 5000 5000 5000	T-5-5, R-8-E WATHE TOWNSHIP AUGLAIZE COUNTY, ONIO
5.89?32'10'W. 96.3 259.40'	S136.30.50
3.673 Acres	187.00: 187.00:
737.02'7 N.69°52'E	97.41'.0 0
LEGENO  IRON PIN SET  R.R. SPINE SET  PK. NAIL	3000
THIS PLAT IS RECORDED IN SURVEY BOOK E", PAGE 312, IN THE AUGUAIZE CO. ENG. OFFICE	ATTEST: Doug Pailert  Doug Freinmart
Signature by a representative of the County Health Dept, denotes compliance with Health Regulations, Signed: Date	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.  Signed:
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:  for political S. D. of:  Date	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.  Signed:  Date
County And Drawn by Schecked by	DOUG Date 8-6-80  OF 2 3 2 (T.5.5; R.6.5)

## SURVEYORS DESCRIPTION

The following described tract of ground is part of the Northwest Quarter of Section 5, Wayne Township, Township Five South, Range Eight East, Auglaise County, Ohio and is more particularly described as follows:

Commencing at a point over a stake found by the Ohio Dept. of Transportation at Station 92+78. on the centerline survey of State Route # 196; said stake being the Northwest corner of Section 8, Wayne Township;

Thence SOO°-OL'W along the centerline of State Route # 196 a distance of 1350.20 feet to a nail over a stone found by ODOT at Sta. 79+47.80 of said center-line survey;

Thence SOO -OS'E along the centerline of S.R. # 196 a distance of 147.50 feet to a spike and the PLACE OF BEGINNING:

Thence continuing along said centerline SOO -- 05'E a distance of 250.00 feet to a spike;

Thence N89°-52'E a distance of 737.02 feet to an iron pin;

Thence NOO°-05'W a distance of 52.00 feet to an iron:pin;

Thence S89°-52'W a distance of 97.41 feet to an iron pin;

Thence NL2°-20'-30"W a distance of 155.24 feet to an iron pin;

Thence N56°-42'-30"W a distance of 217.63 feet to an iron pin; Thence SL4°-23'-30"W a distance of 91.69 feet to an iron;

Thence S59°-32'-10"W a distance of 259-40 feet to a concrete right-of-way

monument in the East right-of-way of S.R. # 196;

Thence S59\*-52'W a distance of 30.00 feet to a spike in the centerline of S.R. # 196 and the PLACE OF BEGINNING.

The above described tract of ground contains 3.673 Acres of which 0.172 Acres has been dedicated for highway purposes. Previous deed reference: Volume 224; Page 568; Auglaize County Recorders Office. Survey recorded in plat book E, page 312, Auglaize County Engineers Office.

Attest:

Doug Reinhart

Professional Surveyor # 6507



Signature by a representative of the County I denotes compliance with Health Regulations.  Signed: Date	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.  Signed:  Date					
Signature by a representative of City with 3 mil diction or Twp. Trustees or Village with zoning denotes approval of this plat. Signed:	jurisdiction	denotes that	this plat n	neets tax m	the County Engineer's I sap plat requirements.	)ont.
Reinhart Surveying Doug Reinhart, P.S. R.R.#6, Wapakoneta, Ohio 45895	County Drawn by	Randy Auglaise	Twp.		Drwg. No. <u>50-20</u>	