

Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of City with 3 mile limit juris-  
diction or Twp. Trustees or Village with zoning jurisdiction  
denotes approval of this plat. Signed: \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

**AUGLAIZE COUNTY**  
**ENGINEERS OFFICE**

Client **ST. MARYS TWP. TRUSTEES**  
County **AUGLAIZE** Twp. **ST. MARYS** Sec. **12 NW 1/4**  
Drawn by **JOHN JAUERT** Scale **1"=50'** Drwg. No. \_\_\_\_\_  
Checked by **D.P.R. & D.C.** Date **AUG. 13<sup>TH</sup>, 1980**  
Sheet **1** of **2**

(T 6 S; R 4 E)

L-327

327

327

# SURVEYORS DESCRIPTION

Scale: \_\_\_\_\_

The following described tract of ground is part of the Northwest Quarter of the Northwest Quarter of Section 12, St. Marys Township, Township Six (6) South, Range Four (4) East, Auglaize County, Ohio and is more particularly described as follows:

The PLACE OF BEGINNING is a monument box at the Northwest corner of Section 12, St. Marys Township; Thence S00°-36'-20"W along the West line of Section 12 and the centerline of County Road # 61 (C.R. # 61 formerly known as Plattner Road) a distance of 350.00 feet to a spike;

Thence S89°-23'-40"E through an iron pin at 33.34 feet in the East right-of-way line of County Road # 61 for a total distance of 234.04 feet to an iron pin;

Thence N00°-36'-20"E; through a P.K. Nail on Tangent, Station 300+33.68 of the centerline of State Route # 29 survey made by the Ohio Department of Transportation at 284.16 feet; through a P.K. Nail in the centerline of State Route # 29 at Sta. 300+30.67 of the centerline survey made by ODOT at a distance of 291.41 feet; through an iron pin in the south right-of-way line of State Route # 29 at 222.77 feet for a total distance of 353.47 feet to an iron pin in the North line of Section 12, St. Marys Township;


Thence S89°-45'-20"W along the north line of Section 12 through a P.K. Nail on the Tangent Sta. 298+79.67 of the centerline survey of State Route # 29 at 138.56 feet for a total distance of 234.06 feet to a monument box at the Northwest corner of Section 12 and the PLACE OF BEGINNING.

The above described tract of ground contains 1.890 Acres of which 0.890 Acres has been previously dedicated for highway purposes. The above described tract of ground is subject to all easements of record. Previous deed reference; Volume 171, Page 331, CT Volume 4, Page 342, Auglaize County Records Office, Survey recorded in Plat Book E, Page 327, Auglaize County Engineers Office.

ATTEST:

*Doug Reinhart*  
Douglas Reinhart

Professional Surveyor # 6507



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

SURVEY MADE BY AUGLAIZE COUNTY  
ENGINEERING DEPARTMENT  
CLAYTON "SKIP" STIMMEL P.E.P.S.  
AUGLAIZE COUNTY ENGINEER

Client St. Marys Township Trustees  
County Auglaize Twp. St. Marys Sec. 12  
Drawn by \_\_\_\_\_ Scale \_\_\_\_\_ Drwg. No. \_\_\_\_\_  
Checked by Doug Crawford Date 8-13-80  
Sheet 2 of 2

(T 6 S R 4 E)

328

328