


R. FOCHT SURVEY

LOCATION




WAYNE TWP.
SECTION 8
T-5-S-R-8-E
AUGLAIZE CO. OHIO

LEGEND

- R.R. SPIKE
- IRON PIPE
- AUG. CO. MON. BOX

ANGLES

- A.. 89° 09' 40"
- B.. 90° 50' 20"
- C.. 89° 09' 40"
- D.. 90° 50' 20"



Thomas W. Steinke

BUCKLAND HOLDEN RD
C.R. 190 NORTH LINE OF SEC.

PRORATED FOR
D.B 193 PROPERTY LINE
PG. 802

N. LINE of D.B 195
PG. 534

Part of D.B 195
PG. 534

2.777 AC.

EXISTING
HOUSE
AND
WELL

Total Half Section 2642.00'

FILE NO 80-1016

EAST WEST HALF SECTION

EAST 1/4 Post
OF SEC

This survey is recorded in Book E Page 352 of the Auglaize Co. Engs. Office

TOWN 5 SOUTH RANGE 8 EAST

SCALE: 1" = 100

AUGLAIZE COUNTY HEALTH DEPT.

AUGLAIZE COUNTY PLANNING COMM.

signature

date

signature

date

JURISDICTION 3 MILE LIMIT OR
TOWNSHIP

AUGLAIZE COUNTY ENGINEER

signature

date

signature

date

CLIENT: RUTH FOCHT

DATE: SEPT 14, 1980

COUNTY: AUGLAIZE

TOWNSHIP: WAYNE

SECTION: EIGHT



THOMAS W. STEINKE & ASSOC., INC.

LAND SURVEYING

LAND DEVELOPMENT

123 W. AUGLAIZE ST. - WAPAKONETA, OHIO 45895

PHONE: 419-738-7421

DESCRIPTION OF 2.777 ACRES

Being 2.777 Acres located in the east half of Section Eight, Wayne Township T5-S--R-8-E Auglaize County Ohio, and being further described as follows.

Commencing at the north/east corner of Section Eight, Wayne Township, Auglaize County, Ohio, said corner being marked by a Auglaize County Monument Box, also being the centerline intersection of Buckland Holden Road (C-R 190 and Moyer Road (T-R 271).

Thence in a southerly direction along the centerline of Moyer Road T-R 271 and the east line of Section Eight a distance of 990.75 feet to a railroad spike and the PLACE OF BEGINNING for the parcel herein described .

Thence continuing along the centerline of Moyer Road (T-R 271) and the east line of Section Eight in a southerly direction a distance of 526.0 feet to a railroad spike, marking the south/east corner of this parcel.

Thence in a westerly direction with and angle to the left, being a interior angle to this parcel of $90^{\circ}50'20''$ a distance of 230.0 feet to a iron pipe, marking the south/west corner of this parcel.

Thence in a northerly direction with an interior angle of $89^{\circ}09'40''$ a distance of 526.0 feet to a iron pipe, marking the north/west corner of this parcel.

Thence in a easterly direction with an interior angle of $90^{\circ}50'20''$ a distance of 230.0 feet to a railroad spike in the centerline of Moyer Road (T-R 271), also being a point on the east line of said section, also being the PLACE OF BEGINNING for this parcel, passing through a iron pipe at 210.0 ft

Containing in all 2.777 Acres and being subject to any and all easements and Right-of-Way of record.

This survey is recorded in Book E Page 352 of the Aug. Co. Eng.'s Office.

Survey and description prepared by Thomas W. Steinke and Assoc. Inc.

123 West Auglaize Street-Wapakoneta, Ohio this 16th day of Sept. 1980.

File No. 80-1016