N	
WEE	N.E. CORNER, N.W. M. SEC. 3, PUBLICA TWO.
S LOCATION FLAN	NOO:43'
PUBLISTA THE RANDONED T-G-S, FT-G-E, AUGUSTEE I ROAD S COUNTY, OMIO	Mos°0520°E
LEGEND IRON PIN SET IRON PIN FOUND R.R. SPIKE SET R.R. SPIKE FOUND	23. Lawer 2
5.88°09'30"E. 381.26' 1.52 ACRES 0.03 ACRE DEDICATED WE FOR ACCESS DRIVE	
THIS PLAT RECORDED IN SURVEY BOOK E, PAGE 354	(13.19') Doug Finder Doug Reinhart Rea. Surveyor 6507
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed:	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date
DOUG REINHART County AND Drawn by Son Checked by	of 2 (T (O S; R (O E)
01004	0 0 4t



SURVEYORS DESCRIPTION

The following described tract of ground is part of the Northwest Quarter of Section 3, Pusheta Township, Township Six South, Range Six East, Auglaize County, Ohio and is more particularly described as follows:

Commencing at the Northeast corner of the Northwest Quarter of Section 3. Pusheta Township; Thence SOO*-43'-50"W along the North-South half-section line of Section 3 a distance of 1088.28 feet to an iron pin in the north right-of-way line of the abandonded T.& O.C. Railroad; Thence N67*-57'-40"W along the said north right-of-way line a distance of 491.94 feet to a spike in the centerline of a dedicated 25' access lane; Thence SO2*-05'-20"W along the centerline of said 25' lane a distance of 270.11 feet to a spike and the PIACE OF BEGINNING:

Thence continuing SO2°-05'-20"W along the centerline of said lane a distance of 115.00 feet to a spike;

Thence S73°-31'W through a spike in the right-of-way line of said access drive at 13.19 feet for a total distance of 356.77 feet to an iron pin; Thence NO1°-27'W a distance of 237.00 feet to an iron pin;

Thence SSS -09'-30 E through an iron pin in the west right-of-way line of the 25' wide access drive at 368.76 feet for a total distance of 381.26 feet to a railroad spike and the PLACE OF BEGINNING.

The above described tract of ground contains 1.52 Acres of which 0.03 Acres is contained in the above mentioned access drive. The above described tract is subject to all easements of record. Tie dimensions and bearings are based on a survey Ben Cartwright, Reg. Surveyor # 5456 and dated March 10, 1971. Previous deed reference: Volume 177, Page 277, Auglaize County Recorders Office. Survey Plat recorded in Survey Book E, Page 354, Auglaize County Engineers Office.

ATTEST: Doug Reinhart

Registered Surveyor # 6507



Signature by a representative of the Count denotes compliance with Health Regulations. Signed:		Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date
Signature by a representative of City with 3 diction or Twp. Trustees or Village with zon denotes approval of this plat. Signed: for political S. D. of:	ing jurisdiction	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date
REINHART SURVEYING DOUG REINHART, P.S. # 6507 R.R. # 6, Wapakoneta, Ohio	County A: Drawn by	Charles Kantner Uglaize Twp. Pusheta Sec. 3 Scale Drwg. No. 50-205 Date 9-3-80 (T 6 S; R 6 E)