
STONE FOUND ON WEST FW L.  SOF ADANDONED FOAD ON EA  WEST & SECTION LINE.	CEAST-WEST YE SEC. LINE
14.91 ACRE  14.91 ACRE  14.91 ACRE  15.52.52.  14.91 ACRE  15.52.52.  15.52.52.  16.60.55.  16.60.5	DOCATION FINE 16.5 WEST  OF EXISTING FENCE LINE  OF EXISTING FENCE  OF EXISTING  OF EXISTING FENCE  OF EXISTING  OF EXISTING FENCE  OF EXISTING FENCE  OF EXISTING FENCE
Signature by a representative of the County Health Dept.  dénotes compliance with Health Regulations.  Signed:	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed:
DOUG REINHART County AND Drawn by 30 Checked by	ARRY TANGEMAN  MCSLAIRE TWP. CERTIAN Sec. 15  PHN JANEARY Scale 1"= 200' Drwg. No.80-708  DRE. Date Oct. 18, 1960  of 2 (T. 7 s; R.4E)



The following described tract of ground is part of the Southwest Quarter of Section 15, German Township, Township Seven South, Range Four East, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box at the Southeast corner of the Southwest Quarter of Section 15, German Township, said box being in the centerline of County Road # 50 (C.R. # 50 formerly known as Amsterdam Road);

Thence S89°-56'-30"W along the south line of Section 15 and the centerline of County Road # 50 a distance of 1317.13 feet to a P.K. Nail;
Thence NOO°-05'W a distance of 1332.78 feet to an iron pin and the PLACE OF BEGINNING:

Thence continuing NOO"-05'W a distance of 1312.78 feet to a spike, said spike being 20.00 feet south of the East-West half-section line;

The noe S89\*-55\*-10"W parallel with the East-West half-section line a distance of 464.13 feet to a spike;

Thence S31°-15'-20"W a distance of 58.58 feet to an iron pin;
Thence S00°-01'E, parallel to the North-South half-section line of the Southwest Quarter of Section 15, a distance of 1262.74 feet to an iron pin;
Thence N89°-55'-50"E a distance of 490.10 feet to an iron pin and the PLACE OF BEGINNING.

The above described tract of ground contains 14.91 Acres and is subject to all easements of record. Previous Deed Reference: Volume 253, Page 706, Auglaize County Recorders Office. Survey filed in Plat Book E, Page 361, Auglaize County Engineers Office. All bearings were based upon a survey done by the Mote Engineering Firm.

ATTEST: Doug Remlast

Doug Heinhart

Professional Surveyor # 6507

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.  Signed:
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:  for political S. D. of:  Date	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.  Signed:  Date

REINHART SURVEYING
Doug Reinhart, P.S.
R.R. # 6, Wapakoneta, Ohio

Client Larry Tangemen County Auglaize Twp. German Sec. 15

Drawn by Scale Drwg. No. 80-200

Checked by Sheet 2 of 2 Pate 10-2-80

(T. 7 S; R 4 E)