



- LEGEND**
- IRON PIN SET
 - IRON PIPE FOUND
 - △ SPIKE SET
 - ▲ SPIKE FOUND
 - ◊ SPIKE OVER STONE

ATTEST: Doug Reinhart
DOUG REINHART
REG. SURVEYOR
Nº 6507

THIS PLAT IS RECORDED IN
SURVEY BOOK E, PAGE 371,
IN THE AUGLAIZE COUNTY
ENGINEER'S OFFICE.

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: _____ Date _____	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: _____ Date _____
Signature by a representative of City with 3 mile limit juris- diction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ for political S. D. of: _____ Date _____	Signature by a representative of the County Engineer's Dept, denotes that this plat meets tax map plat requirements. Signed: _____ Date _____

DOUG REINHART 371 LAND SURVEYING	Client <u>MAURICE BECKER</u>
	County <u>AUGLAIZE</u> Twp. <u>SALEM</u> Sec. <u>21 W.4</u>
	Drawn by <u>JOHN JAUERT</u> Scale <u>1"=60'</u> Drwg. No. <u>80-209</u>
	Checked by <u>D.P.R.</u> Date <u>OCT. 12, 1980</u>
	Sheet <u>1</u> of <u>2</u> 371 (T & S & R & E)



Scale: _____

SURVEYORS DESCRIPTION

The following described tract of ground is part of the West-half of Section 21, Salem Township, Township Four South, Range Four East, Auglaize County Ohio, and is more particularly described as follows:

Commencing at a spike over a stone at the Southwest corner of Section 21, Salem Township, said spike being in the centerline of State Route # 116;
Thence N01°-39'-20"E along the centerline of State Route # 116 and the West line of Section 21 a distance of 2517.47 feet to an iron pin in the centerline of County Road # 226 (C.R.# 226 formerly known as Deep Cut Road);
Thence S89°-24'E along the centerline of County Road # 226 a distance of 2033.68 feet to a spike and the PLACE OF BEGINNING;
Thence continuing S89°-24'E a distance of 100.00 feet to a spike;
Thence N00°-36'E through an iron pin at 28.00 feet for a total distance of 172.00 feet to an iron pin;
Thence S89°-24'E a distance of 253.00 feet to an iron pipe;
Thence N00°-36'E a distance of 28.00 feet to an iron pin;
Thence N89°-24'W a distance of 353.00 feet to an iron pin;
Thence S00°-36'W a distance of 200.00 feet to a spike and the PLACE OF BEGINNING.

The above described tract of ground contains 0.62 Acres of which 0.05 Acres has been dedicated for right-of-way purposes. The above described tract is subject to all easements of record. Previous deed reference: Volume 200, Page 418, Auglaize County Recorders Office. Survey Recorded in Plat Book E, Page 371, Auglaize County Engineers Office.

ATTEST: Doug Reinhart
Doug Reinhart
Professional Surveyor # 6507

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

REINHART SURVEYING
Doug Reinhart, P.S.
R.R. # 6, Wapakoneta, Ohio

Client Maurice Booker
County Auglaize Twp. Salem Sec. 21
Drawn by _____ Scale _____ Drwg. No. 80-209
Checked by _____ Date 10-15-80
Sheet 2 of 2 (T h S: R h E)

372

372