

ticularly described as follows:

Commencing at a spike over the section stone at the Northwest corner of Section 29, Salem Township;

Thence with an assumed bearing of S.00000E. along the West line of Section 29, and the centerline of Township Road 21, a distance

of 1373.91 feet to an iron pin;
Thence N.89°21 '40"E. along the centerline of County Road 218, a distance of 1103.75 feet to a spike which is the PLACE OF BEGINNING; Thence S.00025*10"W. a distance of 141.22 feet to an iron pin;

Thence S.11°50°E. a distance of 109.41 feet to an iron pin; Thence S.00°08°W. a diatance of 126.96 feet to an iron pin; Thence S.89°08°E. a distance of 130.55 feet to an iron pin; Thence N.01040.00 E. a distance of 379.20 feet to a spike in

the centerline of County Road 218;

Thence S.89°21°40"W. along the centerline of County Road 218 a distance of 162.70 feet to a spike which was the PLACE OF BEGINNING.

Containing 1.275 Acres of which 0.093 Acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements. Previous deed reference: Vol.236, Pg.477. The above plat is recorded in Survey Book E, Page 376, in the Auglaize County Engineer's Office.

ATTEST : Long

	Reg. Surveyor #6507
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date	Signature by a representative of the Augilaize County Regional Planning Commission denotes approval of this plat. Signed: Date
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:	Signature by a representative of the County Engineer's Dept.
DOUG REINHART County AUGUATE Twp. SALEM Sec. E9 NW/4 Drawn by John JANERT Scale 1"-100" Drwg. No.80-210 Checked by D.P.R. Date 10-19-80	