PACCETAN TO SECOND TO SECO	Nes: 41E 18:56 18:
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: for political S. D. of: Date	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date
DOUG REINWAST County Aug Drawn by 3c Checked by Sheet 1	DUG & CAROL HOLTBARD CE SUBJECT TWP. LOCAN Sec. 5 DIN JAVENT Scale 1" 60" Drwg. No. 80-213 D.P.R. Date Mov. 25-7-7-0 of 7 (T.A.S.; R.S.E)

CORRECTIVE DESCRIPTION

FOR 2.2 ACRE TRACT



Scale:

The following described tract of ground is part of the Southeast Quarter of Section 5, Logan Township, Township Four (4) South, Range Five (5) East, Auglebre County, Ohio and is more particularly described as follows:

Commencing at a monument box at the Southeast corner of Section 5. Logan Township. said box also being in the centerline of County Road # 91 (C.R. # 91 formerly known as the Moulton-Ft. Amanda Road); Thence NO2°-09'E along the East line of Section 5 and the centerline of C.R. # 91 a distance of 922.00 feet to a rialroad spike and the PLACE OF BEGINNING:

Thence continuing NO2 -09'E along the centerline of C.R. # 91 a distance of 33.91 feet to a railroad spike;

Thence S54°-34'W a distance of 185.91 feet to an iron pin; Thence S65°-41'W a distance of 300.30 feet to an iron pin: Thence S31°-17'W a distance of 61.42 feet to an iron pin;

Thence \$23°-34°W a distance of 127.71 feet to an iron pln; Thence \$67°-02°E a distance of 244.13 feet to a railroad spike in the centerline of Township Toad # 89 (T.R. # 89 formerly known as the Mitchell Road);

Thence N31°+23'E along the centerline of T.R. # 89 a distance of 541.59 feet to a railroad spike in the East line of Section 5 and the centerline of C.R. # 91, said spike also being the PLACE OF BEGINNING.

The above described parcel of ground contains 2.19 Acres of which 0.26 Acres has been dedicated for right-of-way purposes. The above description corrects the error found in existing description found in Volume 211, Page 469, Auglaize County Recorders Office. All existing pins and spikes found from the original survey # 71-5627 by Stimmel & Associates were held for distances and angles with missing pins being reset at corrected distances. Survey filed in Plat Book F, Page 25, Auglaize County Engineers Office.

Doug Reinhart, P.S. # 6507

PARCEL "A" 0.187 ACRES

The following described percel of ground is part of the Southeast Quarter of Section 5, Logan Township, Township Four (4) South, Range Five (5) East, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box at the Southeast corner of Section 5, Logen Township, said box also being in the centerline of County Road # 91, C.R. # 91 formerly known as Moulton Ft. Amanda Road, Thence NO2"-09"E along the East line of Section 5 and the centerline of County Road # 91 a distance of 922.00 feet to a spike, said spike also being in the centerline of Township Road # 89 (T.R. # 89 formerly known as Mitchell Road): Thence S31°-23'W along the centerline of T.R. # 89 a distance of 508.19 feet to a spike and the PLACE OF BEGINNING:

Thence continuing S31 -23 W along said centerline a distance of 33.40 feet to a spike;

Thence N67°-02'W a distance of 244.13 feet to an iron pin; Thence N23°-34'E a distance of 33.04 feet to an iron pin;

Thence S67°-02'E a distance of 245.67 feet to a spike in the centerline of Township Road # 89 and the PLACE OF BEGINNING.

The above described parcel of ground contains 0.187 Acres and is subject to 0.015 Acres of road right-of-way. Previous Deed Reference: See above corrective description for Volume 211, Page 469, Auglaize County Recorders Office. Survey filed in Plat

Signature by a representative of the County Health Dept. denotes compilance with Health Regulations. Signed: Date		Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date		
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: for political S. D. of: Date		Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date		
REINHART SURVEYING Doug Reinhart, P.S.# 6507 R.R. # 6, Wapakoneta, Ohio	County Au		Date2-180	5 No80-213 _s:R_5_8)

F 26

Book F , Page 25, Auglaize County Engineers Office. Doug Poundant

Doug Reinhart, P.S.# 6507



FARCEL "B" MIDDLE 1.00 ACRE

Scale:

The following described tract of ground is part of the Southeast Quarter of Section 5, Logan Township, Township Four (4) South, Range Five (5) East, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box at the Southeast corner of Section 5, Logan Township, said box also being in the centerline of County Road # 91. (C.R. # 91 formerly known as Moulton Ft. Amanda Road); Thence NO2°-09'E along the East line of Section 5 and the centerline of C.R. # 91 a distance of 922.00 feet to a spike, said spike also being in the intersection of the centerline of Township Road # 89(T.R. # 89 formerly known as the Mitchell Road); Thence S31°-23'W along the centerline of T.R. # 89 a distance of 337.27 feet to a spike and the PLACE OF BEGINNING:

Thence continuing S31°-23'W along the centerline of T.R. # 89 a distance of

170.92 feet to a spike;

Thence N67°-02'W a distance of 248.67 feet to an iron pin;

Thence N23°-34'E a distance of 94.67 feet to an iron pin; Thence N31°-17'E a distance of 61.42 feet to an iron pin;

Thence N65°-41'E a distance of 18.56 feet to an iron pin;

Thence S67°-02'E a distance of 251.24 feet to a spike in the centerline of T.R.# 89 and the PLACE OF BEGINNING.

The above described tract of ground contains 1.00 Acres of which O.CS Acres has been dedicated for road right-of-way. Previous deed reference: See above corrective description for Volume 211, Page 469, Auglaize County Recorders Office. Survey filed in Plat Book F, Page 25, Auglaize County Engineers Office. Dog Rinford P.S #6507

PARCEL "C" NORTH 1.00 ACRE

The following described tract of ground is part of the Southeast Quarter of Section 5, Logan Township, Township Four (h), South, Range Five (5) East, Augleize County, Ohio and is more particularly described as fullows:

Commencing at a monument box at the Southeast corner of Section 5, Logan Township, said box being in the centerline of C.R. # 91(C.R. # 91 formerly known as Moulton Ft. Amanda Road); Thence NO2"-09"E along the East line of Section 5 and the centerline of C.R. # 91 a distance of 922.00 feet to a spike and the PLACE OF BEGINNING:

Thence continuing NO2°-09'E along said section line and centerline a distance of

33.91 feet to a spike:

Thence S54°-34'W a distance of 185.91 feet to an iron pin; Thence S65°-41'W a distance of 281.74 feet to an iron pin;

Thence S67°-02'E a distance of 251.24 feet to a spike in the centerline of Township Road # 89(T.R. # 89 formerly known as the Mitchell Road);

Thence N31°-23'E along the centerline of T.R. # 89 a distance of 337.27 feet to a spike in the East line of Section 5 and the centerline of C.R.# 91 and the PLACE OF BEGINNING.

The above described tract of ground contains 1.00 Acres of which 0.165 Acres has been dedicated for road right-of-way. Previous deed reference: See above corrective description for Volume 211, Page 469, Auglaize County Recorders Office. Survey filed in Plat Book F, Page 25, Auglaize County Engineers Office.

Doeg Runlant Doug Reinhart Professional Surveyor # 6507

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date		Signature by a representative of the Auginize County Regional Planning Commission denotes approval of this plat. Signed: Date			
Signature by a representative of City with 3 rediction or Twp. Trustees or Village with zone denotes approval of this plat. Signed: for political S. D. of: D	ing jurisdiction	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date			
REINHART SURVEYING Doug Reinhart Professional Surveyor # 6507 R.R. # 6, Wapakoneta, Ohio	County <u>Au</u> Drawn by <u>Checked by </u>	Holtzapple Sec. 5 Scale Drwg. No. 50-213 Date 2-1-80 (T \(\frac{1}{2} \) S : R \(\frac{5}{2} \) E			

F#27

F27