



\*Signature by a representative of the County Health Dept.  
denotes compliance with Health Regulations.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: \_\_\_\_\_  
for political S. D. of: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.

Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.

Signed: \_\_\_\_\_ Date \_\_\_\_\_

Client NORMAN KANTNER TO DAN KANTNER  
 County AUGLAIZE Twp. PUSHETA Sec. 14  
 Drawn by Jim Emrick Scale 1"=200' Drwg. No.         
 Checked by        Date 5-9-81  
 Sheet 1 of 3 RR#5 Wapxoneto, (T 6 S; R 6 E)

Client NORTHAN KANINER TO DAN KANINER

County AUGLAIZE Twp. PUSHETA Sec. 14

Drawn by Jim Emrick Scale 1"=200 Drwg. No.       

Checked by \_\_\_\_\_ Date 5-9-87

Sheet 1 of 3 RR# 5 Wapokoneta, (T 6 S; R 6 E)

Richard D. Manser

L.S. 6470

~~188~~

1

**KUCK and MORRISEY, INC.**  
CONSULTING ENGINEERS & SURVEYORS  
LIMA, OHIO 45805  
TELEPHONE 228-1735 - AREA CODE 419  
2807 CHAPEL HILL DRIVE

RR# 5 Wapakoneta, Ohio  
CLIENT NORMAN KANTNER

COUNTY AUGLAIZE TOWNSHIP PUSHETA

SECTION 14 T6S R6E LOT NO.

SUBDIVISION

DATE 5-9-81 COMPUTED BY SURVEYED BY JWE

SHEET NO. 2 OF 3

**SURVEYORS DESCRIPTION**  
**PARCEL #1**

The following described tract of land is part of the Northwest Quarter of Section 14, Town 6 South, Range 6 East, Pusheta Township, Auglaize County, Ohio, and is more particularly described as follows.  
Commencing at the corner stone at the Southwest corner of the Northwest Quarter of Section 14, Pusheta Township (Stone being in the center of the Wapakoneta-Freyburg Road #171) Thence North 00°00'00" East, along the center of the Wapakoneta-Freyburg Road #171, 438.15 feet to a railroad spike, this being the PLACE OF BEGINNING.

Thence continuing North 00°00'00" East along the center of the Wapakoneta-Freyburg Road #171, 226.60 feet to a railroad spike.

Thence North 89°24'27" East, (passing through a railroad tie post set at 25.54 feet) 1327.19 feet to a 4" pipe post.

Thence South 00°01'35" West, 661.68 feet to a 18" wood post on the East and West half section line of Section 14, Pusheta Township.

Thence South 89°16'29" West, along the East and West half section line of Section 14, Pusheta Township, 810.38 feet to an iron pipe.

Thence North 00°00'00" East, 451.30 feet to an iron pipe in the center of an open creek.

Thence North 65°00'00" West along the center of the open creek, 47.68 feet to an iron pipe.

Thence North 87°25'00" West along the center of the Open creek, 211.39 feet to an iron pipe.

Thence South 79°22'00" West, 266.65 feet along the center of the open creek, to the railroad spike in the center of the Wapakoneta-Freyburg Road #171, which was the PLACE OF BEGINNING..

The above described tract of land contains 14.65 acres more or less, subject to 0.13 acres dedicated to the public for highway purposes and to all other legal easements of record.

F-189

4

KUCK and MORRISEY, INC.  
CONSULTING ENGINEERS & SURVEYORS  
LIMA, OHIO 45805  
TELEPHONE 228-1735 - AREA CODE 419  
2807 CHAPEL HILL DRIVE

RR#5 Wapakoneta Ohio

CLIENT	NORMAN KANTNER		
COUNTY	AUGLAIZE	TOWNSHIP	PUSHETA
SECTION	14 T 6 S R 6 E	LOT NO.	
SUBDIVISION			
DATE	5-9-81	COMPUTED BY	SURVEYED BY JWE
SHEET NO. 3		OF 3	

SURVEYORS DESCRIPTION  
PARCEL #2

The following described tract of land is part of the Northwest Quarter of Section 14, Town 6 South, Range 6 East, Pusheta Township, Auglaize County, Ohio, and is more particularly described as follows.  
Commencing at the corner stone at the Southwest corner of the Northwest Quarter of Section 14, Pusheta Township, (Stone being in the center of the Wapakoneta-Freyburg Road #171) Thence North 00°00' 00"East, along the center of the Wapakoneta-Freyburg Road #171, 276.00 feet to a railroad spike, this being the PLACE OF BEGINNING.

Thence continuing North 00°00' 00"East along the center of the Wapak-Freyburg Road #171, 162.15 feet to a railroad spike.

Thence North 79°22' 00"East, 266.65 feet to an iron pipe in the center of an open creek.

Thence South 87°25' 00"East, 211.39 feet along the center of the open creek to an iron pipe.

Thence South 65°00' 00"East 47.68 feet along the center of the open creek to an iron pipe.

Thence South 00°00' 00"West, passing through an iron pipe set at 4.50 feet (being the top of the creek bank) 175.30 feet to an iron pipe.

Thence South 89°17' 00"West, (passing through an iron pipe set at 491.54 feet) 516.54 feet to the railroad spike in the center of the Wapakoneta-Freyburg Road #171, which was the PLACE OF BEGINNING.

The above described tract of land contains 2.277 acres more or less, subject to 0.09 acres dedicated to the public for highway purposes and to all other legal easements of record.

F-190