

A circular professional seal for a registered surveyor. The outer ring contains the text "STATE OF OHIO" at the top and "REGISTERED SURVEYOR" at the bottom, separated by two small stars. The center of the seal contains the name "GORDON L. GEESLIN" and the registration number "3372".

"A" = 5 TONE @ S.E. COR. ~ SEC. 18  
 "B" = 8 TONE @ S. 1/4 POST ~ SEC. 18.  
 "C" = IRON @ CENTER ~ SEC. 18.  
 "D" = IRON @ E. 1/4 POST ~ SEC. 18.  
 "E" = RAILROAD SPIKE @ S.W.  
 COR. ~ E. 1/2 ~ SE. 1/4 OF  
 SEC. 18.  
 "F" = RAILROAD SPIKE @ S.W.  
 COR. OF 7.854 AS TRACT  
 "G" = 3/8" IRON BAR FD  
 "H" = 3/8" IRON BAR SET.

SURVEYED BY Gordon L. Geeslin  
GORDON L. GEESLIN  
REGISTERED SURVEYOR  
No 5372

HOWELL SURVEY ~ PART OF THE  
E. 1/2 OF THE S.E. 1/4 OF SECTION 18,  
TOWN 5 SOUTH, RANGE 4 EAST  
(NOBLE TOWNSHIP), AUGLAIZE  
COUNTY, OHIO.

SCALE 1" = 200'

Signature by a representative of the Auglaize County Regional  
Planning Commission denotes approval of this plat.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Signature by a representative of the County Engineer's Dept.  
denotes that this plat meets tax map plat requirements.  
Signed: \_\_\_\_\_ Date \_\_\_\_\_

Client LEO HOWELL  
County ANGLAIZE Twp. NOBLE Sec. 18  
Drawn by GG Scale 1" = 200 Drwg. No. \_\_\_\_\_  
Checked by \_\_\_\_\_ Date 6/14/82  
Sheet 1 of 1 **E302** (T 5 S; R 4 E)

**GORDON L. GEESLIN**

REGISTERED LAND SURVEYOR

PHONE 419/586-6155

June 16, 1982

LEO HOWELL SURVEY DESCRIPTION

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the east half of the southeast quarter of Section 18, Township 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at the corner stone at the southeast corner of said Section 18-

Thence, south  $89^{\circ}48'$  west, along the south line of the southeast quarter of said Section 18 and the centerline of Noble Road, a distance of seven hundred twelve and  $54/100$  (712.54) feet to a railroad spike at the southwest corner of a 7.854 acre tract of land conveyed to Glen E. and Ann F. Donovan by deed recorded in Deed Volume 254, Page 79. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing south  $89^{\circ}48'$  west, along the last described line, a distance of six hundred eighteen and  $83/100$  (618.83) feet to a railroad spike at the southwest corner of the east half of the southeast quarter of said Section 18-

Thence, north  $00^{\circ}00'55''$  east, along the west line of said east half of the southeast quarter of Section 18, a distance of five hundred eighty and  $95/100$  (580.95) feet to a point in the approximate center of an open ditch-

Thence, north  $82^{\circ}21'49''$  east, along the center of said open ditch, a distance of one hundred thirty-three and  $95/100$  (133.95) feet to a point-

Thence, continuing, along the center of said open ditch, north  $76^{\circ}47'22''$  east, a distance of one hundred thirty-six and  $35/100$  (136.35) feet to a point-

Thence, continuing along the center of said open ditch, north  $64^{\circ}49'18''$  east, a distance of three hundred thirty and  $87/100$  (330.87) feet to the northwest corner of the aforementioned Donovan's 7.854 acre tract-

**GORDON L. GEESLIN**

REGISTERED LAND SURVEYOR

PHONE 419/586-6155

Leo Howell Survey

Page Two

June 16, 1982

Thence, south 4°00' east, along said Donovan's west line, a distance of seven hundred seventy and 39/100 (770.39) feet to the place of beginning.

Containing 8.946 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated June, 1982, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin

Registered Surveyor 5372



F309

540 EAST MARKET STREET CELINA, OHIO 45822

F309