


Survey filed in Plat Book F , Page 362, Auglaize
County Engineers Office.



Scale:

SOUTH $\frac{1}{4}$ LINE OF AUGLAIZE STREET
PT. OF FRACTION 2
CITY OF WPAKONETA

DEED: Vol. 235
Pg. 361



CHISELED "4"
IN CONCRETE


105.25'

90°32'30"

CHISELED "4" IN BASE
OF BASKETBALL
SUPPORT POLE

LEGEND

● IRON BAR FD.
○ IRON PIN SET



WEST $\frac{1}{4}$ LINE OF OHIO ST.

E. OHIO STREET
66' R/W

45.00'

90°00'

100'

65.66'

80.00'

90°00'

45.00'

NORTH $\frac{1}{4}$ LINE OF
MECHANIC STREET

33.00'

19.00'

197.25'

90°32'30"

ATTEST: Doug Reinhart
DOUG REINHART
REG. SURVEYOR #6507

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

F362

DOUG REINHART
LAND SURVEYING

Client CHUCK HORMAN
County AUGLAIZE Twp. DUGESBURG Sec. 32
Drawn by J. SAUERT Scale 1"=20' Drwg. No. 82-278A
Checked by _____ Date MARCH, 1983
Sheet 1 of 1 F362 (T. S. R. C. E.)



SURVEYORS DESCRIPTION

Scale: _____

The following described parcel of ground is part of Fraction 2 in the City of Wapakoneta, Ohio, Auglaize County, and is more particularly described as follows:

Commencing at an iron pin at the intersection of the right-of-ways of the North side of Mechanic Street and the West side of Ohio Street; Thence West along the north right-of-way line of Mechanic Street a distance of 216.25 feet to a chiseled "X" in a concrete curb and the PLACE OF BEGINNING;

Thence continuing West along the North right-of-way line of Mechanic Street a distance of 1.00 foot to an iron pin;

Thence with a deflection angle to the right of 90°-00' a distance of 65.66 feet to an chiseled "X" in concrete;

Thence with a deflection angle to the right of 90°-00' a distance of 1.00 foot to a chiseled "X" in concrete;

Thence with a deflection angle to the right of 90°-00' a distance of 65.66 feet to a chiseled "X" in concrete and the PLACE OF BEGINNING.

The above described parcel of ground contains 65.66 square feet and is subject to all easements of record. Survey filed in Plat Book F, Page 362 of the Auglaize County Engineers Office. The above described survey was based upon a survey done for Charles Horman and filed in Plat Book F, Page 216 of the Auglaize County Engineers Office.



ATTEST:

Doug Reinhart
Doug Reinhart

Professional Surveyor # 6507

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

F363

Client South Side Building & Loan
County Auglaize Twp. Duchouquet Sec. _____
Drawn by _____ Scale _____ Drwg. No. 62-272A
Checked by _____ Date 4-5-83
Sheet 2 of 2 F363 (T S R E)