


LEGEND

- "A" = STONE @ N. E. COR. ~ SECTION 26.
- "B" = STONE @ N. W. COR. ~ SECTION 26.
- "C" = RAILROAD SPIKE SET.
- "D" = 5/8" x 30" IRON BAR SET.

SURVEYED BY Gordon L. Geeslin

GORDON L. GEESLIN
REGISTERED SURVEYOR
N^o 5372
CELINA, OHIO



LAMBERT SURVEY ~ PART OF
THE N. E. 1/4 OF SECTION 26, TOWN
6 SOUTH, RANGE 7 EAST (CLAY
TWP.), AUGLAIZE COUNTY, OHIO.
MARCH, 1982 (1983) SCALE 1" = 100'

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed _____ Date _____	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed _____ Date _____
Signature by a representative of City with 3 mile limit juris- diction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed _____ for political S. D. of: _____ Date _____	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed _____ Date _____
GORDON GEESLIN LAND SURVEYOR CELINA, OHIO	Client <u>TERRY LAMBERT</u> County <u>AUGLAIZE</u> Twp. <u>CLAY</u> Sec. <u>26</u> Drawn by <u>GG</u> Scale <u>1"=100</u> Drwg. No. _____ Checked by _____ Date <u>3 MARCH '83</u> Sheet <u>1</u> of <u>1</u> F386 (T 6 S; R 7 E)

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419/586-6155

March 3, 1983

LAMBERT SURVEY DESCRIPTION

Being a parcel of land situated in Clay Township, Auglaize County, Ohio, in the northeast quarter of Section 26, Township 6 South, Range 7 East. Being more particularly described as follows:

Commencing for reference at the corner stone at the northeast corner of said Section 26-

Thence, north 89°48'53" west, along the north line of said Section 26 and the centerline of State Route 720, a distance of eight hundred thirty-four and 65/100 (834.65) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing north 89°48'53" west, along the last described line, a distance of one hundred ninety-two and 06/100 (192.06) feet to a railroad spike-

Thence, south 00°11'07" west, a distance of two hundred ninety-eight and 78/100 (298.78) feet to a 5/8 inch iron bar-

Thence, south 89°48'53" east, a distance of ninety-nine and 53/100 (99.53) feet to a 5/8 inch iron bar-

Thence, north 00°11'07" east, a distance of one hundred forty-nine and 40/100 (149.40) feet to a 5/8 inch iron bar-

Thence, south 89°48'53" east, a distance of ninety-two and 53/100 (92.53) feet to a 5/8 inch iron bar-

Thence, north 00°11'07" east, a distance of one hundred forty-nine and 38/100 (149.38) feet to the place of beginning.

Containing 1.000 acre of land more or less.

Subject to all easements and right-of-way of record.

410 EAST MARKET STREET CELINA OHIO 45822

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419/586-6155

Lambert Survey
March 3, 1983
Page 2

Reference is made to a survey of this area by Gordon L. Geeslin,
Registered Surveyor 5372, dated March, 1983, on file in the
County Engineer's office.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin

Registered Surveyor 5372



410 EAST MARKET STREET CELINA, OHIO 45822