IMON P FOUND 1.9 PHOPERTY	5 FROM ?	REF. I HOW PIW DET AT G.OO'W. OF CORNER A DECTION LINE 10600 T. BARSE'10"E.	
M.W. CORNER.  D. YE. S.W. M. OF  NO. O	0.		9cale:
20.00	0000		
		EB Ac. ROAD The	
COUNTY, ONO	The state of the s	DOUGLAS OF THE PROPERTY OF THE	
O 96" DIE. IRON PO O IRON PIPE FOR A R.R. BRIME DE A R.R. SPIME FOR	7170		
THE ABOVE FLAT 18 IN SURVEY BOOK SO F THE AUGUATES COUNTY	Recorped Sce 188.	REG. ENGINEER LIZANCE	507 70
Signature by a representative of the County denotes compliance with Health Regulations.  Signed:		Signature by a representative of the Auglaize County Replanning Commission denotes approval of this plat.  Signed: Date	ogional
Signature by a representative of City with 3 rediction or Twp. Trustees or Village with zoni denotes approval of this plat. Signed:	ing jurisdiction	Signature by a representative of the County Engineer's denotes that this plat meets tax map plat requirements.  Signed:  Date	Dept.
DOUCE / E. P. REINHART  (1707  PERSONALIZATION	County A	Twp. Frankis Sec. 14	L.

## SURVEYORS DESCRIPTION

The fellowing described parcel of ground is part of the West-half of Section 14. Pusheta Township, Township Six (6) South, Range Six (6) East, Auglaime County, Ohie and is more particularly described as follows

Scale:

Commencing at a spike at the Northwest corner of the S 1/2 of the Southwest Quarter of Section 14. said spike being in the centerline of County Road # 171; Thence S00°22°20°W. a distance of 29.10 feet to a spike at the intersection of County Road # 173; Thence S35°15°E along the centerline of County Road # 173 a distance of 149.90 feet to a spike and the PIACE OF BEGINNING:

Thence N87°15'LO"E a distance of 179.54 feet to an iron pipe;
Thence N00°00'E through an iron pin at 370.60 feet for a total distance of

Thence S89°52°10°E through an iron pin at 100.00 feet, a distance of 106.00 feet to a spike;

Thence 823°55°40°E a distance of 644.56 feet to an iron pin;
Thence S51°42°W a distance of 300.00 feet to a spike in the centerline of
County Road # 173;

Thence N35°18'W along the centerline of C.R. # 173 a distance of 502.32 feet to a spike and the PIACE OF BEGINNING.

The above described percel contains 4.500 Acres and is subject to 0.28 Acres of road right-ef-way. The above described survey is filed in Plat Book 6. Page 122, in the Auglaize County Engineers Office.

ATTEST : Long Rom Let Doug Re Inhart

Professional Surveyor # 6507



Signature by a representative of the County Health denotes compliance with Health Regulations.  Signed: Date	Planning Commission denotes approval of this plat.
Signature by a representative of City with 3 mile lim diction or Twp. Trustees or Village with zoning juris denotes approval of this plat. Signed:	diction denotes that this plat meets tax map plat requirements.
6507 D	lient Ralph Zwiewel  ounty Auglaize Twp. Pusheta Sec. III  rawn by Scale Drwg. No. 83-339  necked by Date 9-19-83