


Scale:



- ATTEST: Doug Reinhardt
DOUG REINHART
REG. SURVEYOR N° 6507
REG. ENGINEER N° 44670

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Client ROBERT MILLER
County AUGLAIZE Twp. DUXBOURG Sec. 34
Drawn by JOHN JAWERT Scale 1"=200' Drwg. No. 83-340
Checked by _____ Date SEPT. 1963
Sheet 1 of 2 G124 (T 5 S; R 6 E)

SURVEYORS DESCRIPTION

The following described parcels of ground are part of the Southwest Quarter of Section 34, Duchouquet Township, Five South, Range Six East, Auglaize County, Ohio and are more particularly described as follows:

13.57 ACRE TRACT

Commencing at an iron pin at the Northwest corner of the Southwest Quarter of Section 34, Duchouquet Township; Thence S89°-10'-40"E a distance of 1323.52 feet to an iron pin; Thence S01°-10'-20"W a distance of 581.23 feet to an iron pin and the PLACE OF BEGINNING;

Thence continuing S01°-10'-20"W a distance of 1896.06 feet to a spike in the centerline of County Road # 33-A;

Thence N56°-34'-40"W along the centerline of County Road # 33-A a distance of 313.85 feet to a P.K. Nail in the center of C.R. # 33-A

Thence N03°-04'-40"W a distance of 1728.58 feet to an iron pin;

Thence S89°-31'-11"E a distance of 393.58 feet to an iron pin and the PLACE OF BEGINNING.

The above described tract contains 13.57 Acres and is subject to 0.22 Acres of road right-of-way. Survey filed in Plat Book C, Page 124, Auglaize County Engineers Office.

18.40 ACRE TRACT

Commencing at an iron pin at the northwest corner of the southwest quarter of Section 34, Duchouquet Township; Thence S89°-10'-40"E a distance of 1323.52 feet to an iron pin; Thence S01°-10'-20"W a distance of 581.23 feet to an iron pin; Thence N89°-31'-11"W a distance of 393.58 feet to an iron pin and the PLACE OF BEGINNING;

Thence S03°-04'-40"E a distance of 1728.58 feet to a P.K. Nail in the centerline of County Road # 33-A;

Thence N56°-34'-40"W along the centerline of County Road # 33-A a distance of 760.29 feet to a spike;

Thence N06°-23'-11"W a distance of 312.14 feet to an iron pin;

Thence N12°-30'-46"E a distance of 339.84 feet to an iron pin;


Thence N59°-42'-20"E a distance of 175.54 feet to an iron pin;

Thence N11°-22'-52"W a distance of 592.38 feet to an iron pin;

Thence S89°-31'-11"E a distance of 468.21 feet to an iron pin and the PLACE OF BEGINNING.

The above described parcel contains 18.40 Acres and is subject to 0.52 Acres of road right-of-way. Survey filed in Plat Book C, Page 124, Auglaize County Engineers Office.

ATTEST: Doug Reinhart
Doug Reinhart
Professional Surveyor # 6507



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed _____ Date _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed _____ Date _____

DOUGLAS P. REINHART

SURVEYOR 6125

Client Robert Miller
County Auglaize Twp. Duchouquet Sec. 346
Drawn by _____ Scale _____ Drwg. No. 83-340
Checked by _____ Date 9-20-83
Sheet 2 of 2 6125 (T 5 S; R 6 E)