

Survey in NE 1/4 Sec. 6, T55-R8E, Wayne Twp.
Auglaize County, Ohio

NW 1/4 NE 1/4 Sec. 6

The following described parcel of land is situated in the North-east quarter, Section six, Township five South - Range eight East, Wayne Township, Auglaize County, Ohio, and is more particularly described as follows:

Commencing at the nail over the stone found by the County Engineer at the Northwest corner of said quarter in the centerline of County Road 200; thence North eighty-nine degrees thirty-four minutes thirty seconds East (N89°34'30"E) (from prior survey of grantors tract) thirty (30.00) feet to a spike found; thence South zero degrees four minutes forty-five seconds West (S0°04'45"W) parallel with the west line of said quarter nine hundred four and forty hundredths (904.40) feet to an iron pin found; thence North eighty-nine degrees twelve minutes zero seconds East (N89°12'00"E) four hundred seventy-eight and fifty hundredths (478.50) feet to an iron pin found at THE PLACE OF BEGINNING;

thence North eighty-nine degrees forty-four minutes one seconds East (N89°44'01"E) four hundred fifteen and sixty-one hundredths (415.61) feet to a four inch steel post found; thence South zero degrees seven minutes fifteen seconds West (S0°07'15"W) four hundred eighteen and eighty-eight hundredths (418.88) feet through an eight inch square wood post found to the South line of the grantors tract; thence South eighty-nine degrees forty-one minutes fifty-five seconds West (S89°41'55"W) four hundred thirteen and seven hundredths (413.07) feet to an iron pin found; thence North zero degrees thirteen minutes thirty-five seconds West (N0°13'35"W) four hundred nineteen and twelve hundredths (419.12) feet to the place of beginning containing three and ninety-eight hundredths (3.98) acres, more or less, subject to all easements and restrictions of record.

All 1/2" re-rods set and called for above are topped with a permamark plastic cap stamped: LS 5772.

This description and plat represents a survey made under my supervision on October 27, 1983, and all markers called for above are in place.

LEGEND

- = Iron Pin found
- = Spike Found
- = Iron Pin Found
- = 8" Square Wood Post
- ▲ = 4" Steel Post
- △ = Nail found over Stone

George E. Woolley
Registered Surveyor No. 5772

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

Accu-Trace Land Surveys Inc.
2833 Ft. Amanda Rd.
P.O. Box 11
Lima, Ohio 45802

Client Robert Fetter
County Auglaize Twp. Wayne Sec. 6
Drawn by AEW Scale 1" = 200' Drwg. No. _____
Checked by _____ Date 11-2-83
Sheet _____ of _____ 6145 (T 5 S; R 8 E)