


LOCATION SKETCH



E COUNTY ROAD NO 33-A

SECTION 33 - D

N. 80° 37' E.

220.00

ARC = 180.00
CHORD = 179.94
BEARS = N. 80° 14' 18" E.

CURVE DATA

$\Delta = 1^\circ 37'$
 $R = 42,791.85$
 $T = 606.29$



4.000 ACRES

STA. 242+67.45

STA. 244+87.45

STA. 245+53

N. 03° 52' 28" W. ~ 418.51'

S. 86° 07' 32" W. ~ 398.13'

S. 03° 52' 28" E. ~ 450.53'

N. 89° 21' 01" E. ~ 2381.26'

N. 89° 21' 01" E. ~ 2381.26'

S. LINE ~ SEC. 33 & N. LINE ~ FORMER N.Y.C. RR.

LEGEND

- "A" = IRON BAR IN MON. BOX @ S.W. COR. ~ SEC. 33
- "B" = POINT IN & BAY RD. & SEE SURVEY BY C. MENDERINK, REG. SURVEYOR 3151, DATED SEPT. 25, 1965.
- "C" = RIGHT-OF-WAY MON'S. FOUND,
- "D" = RAILROAD SPIKE SET
- "E" = 3/8" x 30" IRON BAR SET.

SURVEYED BY Gordon L. Geeslin

GORDON L. GEESLIN
REGISTERED SURVEYOR
NO 5372
CELINA, OHIO

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

GORDON L. GEESLIN
LAND SURVEYOR
CELINA, OH.

Client JOHN HALL
County AUGLAIZE Twp. MOULTON Sec. 33
Drawn by GG Scale 1" = 100' Drwg. No. _____
Checked by _____ Date 14 DEC. 1983
Sheet 1 of 1 G-173 (T 5 S; R 5 E)

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

December 15, 1983

RIEBESELL SURVEY DESCRIPTION

Being a parcel of land situated in Moulton Township, Auglaize County, Ohio, in the southeast quarter of Section 33, Township 5 South, Range 5 East. Being more particularly described as follows:

Commencing for reference at an iron bar in a monument box at the southwest corner of said Section 33-

Thence, north $89^{\circ}21'01''$ east, along the south line of said Section 33, a distance of three thousand two hundred ninety-six and $93/100$ (3296.93) feet to a point-

Thence, north $03^{\circ}52'28''$ west, a distance of eight hundred fifty-six and $54/100$ (856.54) feet to a $5/8$ inch iron bar. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing north $03^{\circ}52'28''$ west, a distance of four hundred eighteen and $51/100$ (418.51) feet to a railroad spike in the centerline of County Road 33-A. Said point being at centerline station 242 + 67.45-

Thence, north $80^{\circ}37'$ east, along said centerline of County Road 33-A, a distance of two hundred twenty (220.00) feet to a railroad spike at the P.C. of a curve to the right having a radius of 42,971.85 feet and a delta angle of $01^{\circ}37'$ -

Thence, along said curve in the centerline of County Road 33-A, a distance of one hundred eighty (180.00) feet to a railroad spike. the chord to the last described call bears north $80^{\circ}44'18''$ east, a distance of one hundred seventy-nine and $94/100$ (179.94) feet-

Thence, south $03^{\circ}52'28''$ east, a distance of four hundred fifty-six and $53/100$ (456.53) feet to a $5/8$ inch iron bar-

Thence, south $86^{\circ}07'32''$ west, a distance of three hundred ninety-eight and $13/100$ (398.13) feet to the place of beginning.

Containing 4.000 acres of land more or less.


Subject to a 50.00 foot right-of-way off the entire north end for highway purposes and all other easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated December 14, 1983, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



540 EAST MARKET STREET CELINA, OHIO 45822