

Commencing at a monument box at the Northeast corner of the Northeast Quarter of Section 31, Goshen Township;

Thence S.00°10'E. along the East line of Section 31, Goshen Township, a distance of 1,318.84 feet to an iron pin which is the PLACE OF BEGINNING;

Thence continuing S.00°10'E. along the East line of Section 31, Goshen Township, a distance of 383.28 feet to an iron pin;

Thence S.89°45'W. a distance of 852.04 feet to an iron pin, passing thru a spike at 25.00 feet in the centerline of County Road 261 (the Waynesfield Road);

Thence N.00°55'W. a distance of 386.17 feet to an iron pin; Thence N.89°56'30"E. a distance of 857.10 feet to an iron pin in the East line of Section 31, Goshen Township, passing thru a spike at 832.10 feet in the centerline of County Road 261, said iron pin being the true PLACE OF BEGINNING.

Containing in all 7.547 acres of which 0.44 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements of record. Previous deed reference: Vol.222, Pg.302. This plat is recorded in survey book 6, page 268, in the Auglaize County Engineers Office.

ATTEST

Signature by a representative of the County Health Dept.

Signature by a representative of the County Health Dept.

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:

Signature by a representative of City with 3 mile limit jurisdiction denotes approval of this plat. Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed:

Date

Date

Client ARRY	ンタン国際プトクロ	D
County August	Twp. Care a val	Sec. ">\
Drawn by 3.	BT Scale 12 20	O' Drag No BA-356
Checked by	Date	MAY EON 1904
Sheet 2 of 2	-G-268	(T 5 S; R 6 E)

Doug Reinhart

Reg. Surveyor No. 6507