


LEGEND

- "A" = MON. BOX @ CENTER OF SEC. 30.
- "B" = " " " " N. $\frac{1}{4}$ POST ~ SEC. 30.
- "C" = " " " " E. $\frac{1}{4}$ POST ~ SEC. 30.
- "D" = RAILROAD SPIKE SET.
- "E" = $\frac{5}{8}$ " x 30" IRON BAR SET.
- "F" = CORNER POST FD 0.41' S. OF & 0.46' W. OF CORNER.
- "G" = CORNER POST FOUND 3.23' S. OF & 2.35' E. OF CORNER

LOCATION SKETCH



SECTION 30

SURVEYED BY Gordon L. Geeslin
 GORDON L. GEESLIN
 REGISTERED SURVEYOR
 NO 5372
 ~ CELINA, OHIO ~

THOMPSON SURVEY ~ PART OF W. $\frac{1}{2}$ OF THE N.E. $\frac{1}{4}$ OF SECTION 30, TOWN 5 SOUTH, RANGE 4 EAST (NOBLE TWP), AUGLAIZE COUNTY, OHIO.

JULY 11, 1984

SCALE 1" = 200'

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419/586-6155

July 11, 1984

THOMPSON SURVEY DESCRIPTION (TRACT "A")

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the west half of the northeast quarter of Section 30, Town 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at an iron bar in the monument box at the center of said Section 30-

Thence, north $00^{\circ}01'37''$ west, along the west line of the northeast quarter of said Section 30 and the centerline of Koenig Road, a distance of six hundred sixty-nine and $10/100$ (669.10) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing north $00^{\circ}01'37''$ west, along the last described line, a distance of nine hundred ninety two and $81/100$ (992.81) feet to a railroad spike-

Thence, north $89^{\circ}59'49''$ east, along the north line of the south half of the south half of the northwest quarter of the northeast quarter of said Section 30, a distance of one thousand three hundred thirty and $93/100$ (1330.93) feet to a point-

Thence, south $00^{\circ}00'50''$ east, along the east line of the west half of the northeast quarter of said Section 30, a distance of one thousand six hundred sixty-two and $62/100$ (1662.62) feet to a point in the south line of the northeast quarter of said Section 30-

Thence, north $89^{\circ}58'21''$ west, along the south line of the northeast quarter of said Section 30, a distance of one thousand eighty-four and $75/100$ (1084.75) feet to a $5/8$ inch iron bar-

Thence, north $00^{\circ}01'37''$ west, a distance of one hundred twenty-five and $80/100$ (125.80) feet to a $5/8$ inch iron bar-

Thence, north $89^{\circ}58'21''$ west, a distance of eighty-nine and $90/100$ (89.90) feet to a $5/8$ inch iron bar-

Thence, north $01^{\circ}26'02''$ east, a distance of three hundred twenty-two and $41/100$ (322.41) feet to a $5/8$ inch iron bar in the south line of a 1.12 acre tract of land conveyed to Robert and Janet Thompson by deed recorded in Deed Volume 186, page 875-

Thence, north $89^{\circ}40'23''$ east, along said Thompson's south line, a distance of sixty-eight and $88/100$ (68.88) feet to a $5/8$ inch iron bar at the southeast corner thereof-

Thence, north $00^{\circ}01'37''$ west, along said Thompson's east line and the extension thereof, a distance of two hundred twenty-two and (222.00) feet to a $5/8$ inch iron bar-

Continued page 2.

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419/586-6155

2

THOMPSON SURVEY DESCRIPTION (TRACT "A") CONTINUED

Thence, south $89^{\circ}40'23''$ west, a distance of two hundred thirty-three (233.00) feet to the place of beginning.

Containing 47.702 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated July 11, 1984, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin
Gordon L. Geeslin
Registered Surveyor 5372



540 EAST MARKET STREET CELINA, OHIO 45822

6-344

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419/586-6155

July 11, 1984

THOMPSON SURVEY DESCRIPTION (TRACT "B")

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the west half of the northeast quarter of Section 30, Town 5 South, Range 4 East. Being more particularly described as follows:

Beginning at an iron bar in the monument box at the center of said Section 30-

Thence, north $00^{\circ}01'37''$ west, along the west line of the northeast quarter of said Section 30 and the centerline of Koenig Road, a distance of four hundred forty-seven and $10/100$ (447.10) feet to a railroad spike at the southwest corner of a 1.12 acre tract of land conveyed to Robert and Janet Thompson by deed recorded in Deed Volume 186, page 875-

Thence, north $89^{\circ}40'23''$ east, along said Thompson's south line, a distance of one hundred sixty-four and $12/100$ (164.12) feet to a $5/8$ inch iron bar-

Thence, south $01^{\circ}26'02''$ west, a distance of three hundred twenty-two and $41/100$ (322.41) feet to a $5/8$ inch iron bar-

Thence, south $89^{\circ}58'21''$ east, a distance of eighty-nine and $90/100$ (89.90) feet to a $5/8$ inch iron bar-

Thence, south $00^{\circ}01'37''$ east, a distance of one hundred twenty-five and $80/100$ (125.80) feet to a $5/8$ inch iron bar in the south line of the northeast quarter of said Section 30-

Thence, north $89^{\circ}58'21''$ west, along said south line of the northeast quarter of Section 30, a distance of two hundred forty-five and $80/100$ (245.80) feet to the place of beginning.

Containing 1.892 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated July 11, 1984, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin
Gordon L. Geeslin
Registered Surveyor 5372



540 EAST MARKET STREET CELINA, OHIO 45822

G-345

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419/586-6155

July 11, 1984

THOMPSON SURVEY DESCRIPTION (TRACT "C")

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the west half of the northeast quarter of Section 30, Town 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at an iron bar in the monument box at the center of said Section 30-

Thence, north $00^{\circ}01'37''$ west, along the west line of the northeast quarter of said Section 30 and the centerline of Koenig Road, a distance of six hundred fifty-seven and $10/100$ (657.10) feet to the northwest corner of a 1.12 acre tract of land conveyed to Robert and Janet Thompson by deed recorded in Deed Volume 186, page 875. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing north $00^{\circ}01'37''$ west, along the last described line, a distance of twelve (12.00) feet to a railroad spike-

Thence, north $89^{\circ}40'23''$ east, a distance of two hundred thirty-three (233.00) feet to a $5/8$ inch iron bar-

Thence, south $00^{\circ}01'37''$ east, a distance of twelve (12.00) feet to the northeast corner of the afore mentioned Thompson tract-

Thence, south $89^{\circ}40'23''$ west, along said Thompson's north line, a distance of two hundred thirty-three (233.00) feet to the place of beginning.

Containing 0.064 acre of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated July 11, 1984, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin
Gordon L. Geeslin
Registered Surveyor 5372

