

Section 26 T-6-S R-6-E Pusheta Township

Shelby-Auglaize Line ↑ Auglaize County

1/2 Section Line

1/2 Section Line

N/W Cor
S/W Qtr
Sec 26

N/E Cor
S/W Qtr.
Sec 26

Angles

- "A" 89° 27' 20" (Calc)
- "B" 90° 32' 40"
- "C" 89° 27' 20"
- "D" 90° 32' 40"
- "E" 91° 31' 30" (Actual)
- "F" 89° 23' 50" (Actual)
- "G" 89° 26' 10" (Calc)

North

Scale: 1" = 200'

File No 9-7-84

Prepared by

Thomas W. Steinke
Botkins - Ohio

Thomas W Steinke
Sept 17, 1984

Edison Schuman
DB. 143 PG 563

Agnes Gehrllich

DB 199 PG. 821
" 217 " 244

Legend

- = County Monument Box
- = Railroad Spike Set
- = Iron Pin Set

This parcel contains an
existing home, well and
sewage system

1.5082 Ac

40' R/W
Southland Road

S/E Cor.
S/W Qtr.
Sec 26 "E"

S/W Cor
Sec. 26

STR #90

Section Line

2647.89

1323.95

661.97

Shelby Co.
Auglaize Co.

Sidney - Fryburg Road

1/2 Section Line

TR# 173

G 364

Being 1.5082 Acres Located in the south-west quarter of Section 26, Town-6-South, Range-6-East, Pusheta Township, Auglaize County, Ohio and being further described as follows:

Commencing at a monument box located at the south-east corner of the south-west quarter of Section 26;

Thence, west along the south Line of Section 26 and the center Line of T.R.# 90, a distance of 354.97 feet to the Place Of Beginning;

Thence, continuing west along said center Line and section Line, a distance of 307.00 feet to a railroad spike;

Thence, north with an interior angle to this parcel of $89^{\circ}27'20''$, a distance of 214.00 feet to an iron pin;

Thence, east with an interior angle to this parcel of $90^{\circ}32'40''$, a distance of 307.00 feet to an iron pin;

Thence, south with an interior angle to this parcel of $89^{\circ}27'20''$, a distance of 214.00 feet to the Place Of Beginning.

Containing in all 1.5082 Acres and being Subject to all Legal easements and rights-of-way of record.

Survey and description prepared by Thomas W. Steinke this 17th day of September, 1984