

THIS PLAT IS RECORDED IN SURVEY BOOK 2, PAGE 392, IN THE AUGLAIZE COUNTY ENGINEERS OFFICE.

STATE ROUTE 197


STONE FOUND & REF. BY
STATE @ N.W. CORNER
OF SECTION 36

Scale:

1"=600'

LOCATION PLAN

SECTION 36



T-4-S, R-4-E, SALEM
TOWNSHIP, AUGLAIZE
COUNTY, OHIO

1/2 SECTION
LINE

IRON PIN FOUND AT
THE W. 1/4 CORNER OF
SECTION 36, SALEM
TOWNSHIP (SEE PLAT BOOK 2,
Pg. 391, AUGLAIZE CTY. ENG. OFFICE)

5/8" x 30" IRON PINS WERE SET BY
ME ALONG THE WEST LINE OF THE S.W. 1/4
OF SECTION 36, SALEM TOWNSHIP, AT
APPROXIMATELY 400' INTERVALS, ON
12-8-84.


ATTEST:

Doug Reinhart

DOUG REINHART

REG. ENGINEER NO 44670

REG. SURVEYOR NO 6570



STONE FOUND AT THE
S.W. CORNER OF SEC. 36

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.

Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.

Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____

for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.

Signed: _____ Date: _____

DOUG REINHART
LAND SURVEYING

Client RICHARD HOVERMAN

County AUGLAIZE Twp. SALEM Sec. 36 60.14

Drawn by S. J. BERRY Scale 1"=600' Drwg. No. _____

Checked by _____ Date 12-9-84

Sheet 1 of 1

392

(T 4 S; R 4 E)