NEW ARMSTR	OUG DIRP	ORT PARCEL	No 10
¢	COR STATE		
M.W. COMUER, E.YE, S. S.E.YA, N.W.YA, SECTION 29 WASUIT	SE DO TOWNELLINGS TO THE PARTY OF THE PARTY	SPIKE OU STONE FOUND O.D.O.T.) AT TO NORTH YO CO SECTION EQ.	WE CEN
		RR SPIKE FOUNT IKON PIN SET CONCRETE MONUM	62
2 3.150 ACT. 8.7 SCHROOM DOWN 228	BARBARA 3.	268.857	
5.68° 0.6	KYE OF OTON	8.77-18'00'\	
This Plat is Received in the County	COURTY ENG	HUER BOOK CO, NUEER'S OFFICE	PAGE 725,
notes compliance with Health Regulations. med: mature by a representative of City with 3 retion or Twp. Trustees or Village with zonimotes approval of this plat. Signed: political S. D. of: D	nile limit juris- ng jurisdiction Signat denote	ure by a representative of the Aung Commission denotes approval of the Court of the	unty Engineer's Dept.
AUGILAIRE COUNTY NGINEER'S OFFICE 9, 125	County S. 300	OF COUNTY COMP TRE TWP. WASLINGT STRIT Scale L'-LOO' I COUPORD Date AU	orfice. 29

NEIL ARMSTRONG AIRPORT PARCEL #16 KENNETH L. & BARBARA J. SCHROER



Being a parcel of land located in the East 1/2 of the Southeast 1/4 of the Northwest 1/4 of Section 29, Town 6 South, Range 5 East, Washington Township, Auglaize County, Ohio further described as follows:

Scale:

Commencing for reference at a railroad spike over a stone at the Northeast Corner of the Northwest 1/4 of Section 29; thence S 00°46'23" W along the East line of the Northwest 1/4 of Section 29 a distance of 1708.58 feet to a point on one of the Northerly lines as described in Deed Volume 228 Page 925;

Thence S 77°18'00" W along one of the lines as described in Deed Volume 228 Page 925 a distance of 268.85 feet to a concrete monument, at one of the corners as described in Deed Volume 228 Page 925 and the PLACE OF BEGINNING;

Thence S 12°42'00" E 50.00 feet to an iron pin;

Thence S 77°18'00" Wa distance of 26.57 feet to an iron pin;

Thence S 68°46'10" W a distance of 417.37 feet to an iron pin, said pin being on the Westerly line as described in Deed Volume 228 Page 925 and the West line of the East 1/2 of the Southeast 1/4 of the Northwest 1/4 of Section 29;

Thence N 00°47'55" E along the Westerly line as described in Deed Volume 228 Page 925 and the West line of the East 1/2 of the Southeast 1/4 of the Northwest 1/4 of Section 29, a distance of 634.79 feet to an iron pin at the Northwesterly corner as described in Deed Volume 228 Page 925 said corner being the Northwest Corner of the East 1/2 of the Southease 1/4 of the Northwest 1/4 of Section 29;

Thence S 42°38'51" E along one of the lines as described in Deed Volume 228 Page 925, a distance of 583.21 feet to the concrete monument, which was the TRUE PLACE OF BEGINNING.

Containing 3.156 acres more or less and subject to all easement of record and/or in use on said premises.

Previous Deed Volume 228 Page 925.



ATTEST:

John W. Jauert

Professional Surveyor No. 6920

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed Date	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed Date
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: Date	Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed Date

		Chent Board of County Commissioners		
STATZE CORNEY		County we Two Washington Sec 29		
ENGINEER OFFICE		Drawn by I lask it Scale 1 100 Drwg No		
		Checkee by D. Cristand Date August 1986		
		of the control of the		