



LEGEND

- "A" = IRREGULARLY SHAPED PIECE OF IRON - SEE SURVEY BOOK 3, PG. 211, DATED 1910.
- "B" = IRON BAR IN MON. BOX.
- "C" = RAILROAD SPIKE SET.
- "D" = 5/8" X 30" IRON BAR SET.
- "E" = WOOD COR. POST

SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR
NO 5372

AUFDERHAAR SURVEY
PART OF THE N.E. 1/4 OF SECTION 6,
TOWN 6 SOUTH, RANGE 5 EAST (WASHINGTON TWP.), AUGLAIZE COUNTY, OHIO.
JUNE 20, 1986 SCALE 1" = 100'

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

GORDON L. GEESLIN
LAND SURVEYOR
CELINA, OHIO

Client VERYL CISCO
County AUGLAIZE Twp. WASHINGTON Sec. 6
Drawn by G.G. Scale 1" = 100' Drwg. No. _____
Checked by _____ Date 6-20-86
Sheet 1 of 1 6-801 (T 6 S; R 5 E)

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

June 20, 1986

AUFDERHAAR SURVEY

Being a parcel of land situated in Washington Township, Auglaize County, Ohio, in the northeast quarter of Section 6, Township 6 South, Range 5 East. Being more particularly described as follows:

Commencing for reference at an irregularly shaped piece of iron at the northeast corner of said Section 6-

Thence, south, along the east line of the northeast quarter of said Section 6 and the centerline of Glynwood-New Knoxville Road, a distance of one thousand six hundred forty-two and 05/100 (1642.05) feet to a railroad spike. Said point being the place of beginning for the herein described parcel-

Thence, continuing, south, along the last described line, a distance of one hundred twenty (120.00) feet to a railroad spike-

Thence, south $89^{\circ}25'39''$ west, a distance of two hundred (200.00) feet to a 5/8 inch iron bar-

Thence, north, a distance of one hundred twenty (120.00) feet to a 5/8 inch iron bar-

Thence, north $89^{\circ}25'39''$ east, a distance of two hundred (200.00) feet to the place of beginning.

Containing 0.551 acre of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated June 20, 1986 on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372



G802

101 SOUTH LEBLOND STREET

CELINA, OHIO 45822