

SURVEYOR'S DESCRIPTION



Scale:

The following described tract of land is part of the Southwest Quarter of Section Thirty-three (33), Moulton Township, Township Five (5) South, Range Five (5) East, Auglaize County, Ohio, and is more particularly described as follows;

Commencing at an Auglaize County Monument Box located at the Southwest Corner of the Southwest Quarter of Section Thirty-three (33), Moulton Township, Township Five (5) South, Range Five (5) East, Auglaize County, Ohio;

thence with an assumed bearing of N. 00°-00'-00" E. along the West line of the Southwest Quarter of said Section 33, and the centerline of County Road #91, Moulton-Ft. Amanda Road, for a distance of 730.49 feet to a P.K. Nail located on the centerline of County Road #33-A;

thence with a bearing of N. 80°-16'-00" E. along the centerline of County Road #33-A for a distance of 305.94 feet to a P.K. Nail and the PLACE OF BEGINNING;

thence continuing with a bearing of N. $80^{\circ}-16'-00''$ E. along the centerline of County Road #33-A for a distance of 121.48 feet to a P.K. Nail situated at the P.C. of a Curve to the left having the following properties: Delta Angle = $00^{\circ}-56'-00''$, Degree of Curve (D°) = $00^{\circ}-08'-00''$, Tangent Length (T) = 350.00 feet, Length of Curve (L) = 700.00 feet, and Radius (R) = 42,971.90 feet, said P.C. having a station of 214+31.82;

thence continuing along the centerline of said curve to a P.K. Nail having a chord distance of 322.96 feet and a bearing of N. 80°-03;-00" E.;

thence with a bearing of S. 06° -57'-00" E. for a distance of 403.22 feet to an iron pin, and passing thru a P.K. Nail on the tangent of said Curve at 1.21 feet, and passing thru an iron pin on the South right-of-way line of County Road #33-A at 51.27 feet;

thence with a bearing of N. $89^{\circ}-30^{\circ}-00^{\circ}$ E. for a distance of 140.00 feet to an iron pin;

thence with a bearing of N. $00^{\circ}-30'-00''$ W. for a distance of 172.00 feet to an iron pin;

thence with a bearing of N. $79^{\circ}-20^{\circ}-00^{\circ}$ E. for a distance of 95.00 feet to an iron pin;

thence with a bearing of N. $00^{\circ}-30'-00''$ W. for a distance of 260.30 feet to a P.K. Nail on the centerline of County Road #33-A, and passing thru an iron pin on the South right-of-way line of County Road #33-A at 209.39 feet, and passing thru a P.K. Nail on the tangent of said Curve at 260.19 feet;

thence along the centerline of the curve of County Road #33-A to a P.K. Nail having a chord distance of 94.11 feet and a bearing of N. 79°-23'-49" E., said P.K. Nail being the P.T. of the aforementioned curve and having a station of 221+31.82;

thence continuing along the centerline of County Road #33-A with a bearing of N. 79°-20'-00" E. for a distance of 221.68 feet to a P.K. Nail;

(continued next page)

N				
Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date	Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed: Date			
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed:	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date			
County At Drawn by 1	rry Longsworth uglaize Twp. Moulton Sec. 33 Kevin Schnell Scale As Shown Drwg. No. 88-340 John W. Jauert Date 3/13/88 of 3 H-209 (T_5 S; R_5 E)			



(Surveyor's Description Continued from page 2/3)

Scale:

thence with a bearing of S. 00°-03'-56" E. for a distance of 952.98 feet to an iron pin, and passing thru an iron pin on the South right-of-way line of County Road #33-A at 55.96 feet;

thence with a bearing of S. 89°-21'-48" W. along the South line of the Southwest Quarter of Section 33, and the North right-of-way line of the abandoned Penn Central Railroad, for a distance of 1,027.12 feet to an iron pin;

thence with a bearing of N. 00°-02'-24" W. for a distance of 778.86 feet to a P.K. Nail on the centerline of County Road #33-A, and passing thru an iron pin on the South right-of-way line of County Road #33-A at 728.14 feet, said P.K. Nail being the PLACE OF BEGINNING.

The above described tract of land contains, in all, 18.251 Acres and is subject to acres being previously dedicated for highway right-of-way purposes. This tract of land is also subject to all legal easements, reservations, or restrictions, if any, upon said property. Previous Deed References: VOLUME 222, PAGE 88, Auglaize County Recorder's Office. This Plat and Description is Recorded in Survey Book H, Page 208, in the Auglaize County Engineer's Office.

JAUERT 6920 COSTERED OF THE PROPERTY OF THE PR

ATTEST:

John W. Jauert Professional Surveyor

No. 6920

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date	Signature by a (representative of the) County Commissioner(s) denotes approval of this plat. Signed: Date
Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date	Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date

ClientL	arry Lo	ngsv	vorth			
County				Moulton	Sec	33
Drawn by	Kevin	Schr	nell Scale	As Shown	Drwg. No.	. <u>88-34</u> 0
Checked by	John	W	Jauert	Date	3/13/88	
Sheet_3						