

P.K. NAIL FOUND IN THE BOTTOM OF AN OBLITERATED CORNER POST AT THE NORTHWEST CORNER OF SEC. 19


Scale:

1"=330'

E COUNTY ROAD 228 (DEEP CUT ROAD, 60' R/W)
860.70' S.89°30'E. 63.98' 834.52' S.89°30'E.

LOCATION PLAN

SECTION 19



LOGAN TOWNSHIP
T-4-S, R-5-E, AUGLAIZE
COUNTY, OHIO

LEGEND

- IRON PIN SET
- IRON PIN FOUND
- △ R.R. SPIKE SET
- EXISTING CORNER POST

IRON PIN SET IN BOTTOM OF AN OBLITERATED CORNER POST AT THE WEST QUARTER CORNER OF SECTION 19.

THIS SURVEY IS RECORDED IN SURVEY BOOK "W", PAGE 243, IN THE AUGLAIZE COUNTY ENG. OFFICE.



ATTEST:

JOHN W. JAUERT
PROFESSIONAL SURVEYOR NO. 6920

1.00°17'52"E.
1,345.29'

1.00°17'52"E.
1,322.29'

FARM GROUND
(30.46 AC.)

1/2 SECTION LINE
1,020.17'
S.89°53'52"W.

WOODS
(30.98 AC.)

1,020.17'
N.89°53'52"W.

1,338.20'
S.00°29'W.

1,322.29'
S.00°17'52"W.

IRON PIN FOUND AT CENTER OF SECTION 19, LOGAN TOWNSHIP

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s) denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

JAUERT
SURVEYING

Client JOE MACK
County AUGLAIZE Twp. LOGAN Sec. 19
Drawn by S. JAUERT Scale 1"=330' Drwg. No. 88-362-A
Checked by _____ Date MAY 10TH 1988
Sheet 1 of 2 H-243 (T 4 S; R 5 E)



SURVEYOR'S DESCRIPTION

Scale: _____

The following described tract of land is part of the Northwest Fractional Quarter and part of the Southwest Fractional Quarter of Section 19, Town 4 South, Range 5 East, Logan Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a P.K. nail in the center of an obliterated concrete corner post at the Northwest corner of the Northwest Fractional Quarter of Section 19;

thence S.00°39'09"W. along the West line of the Northwest Fractional Quarter of Section 19, Logan Township, a distance of 1,309.39 feet to an iron pin found;

thence S.89°30'E., along the centerline of County Road 228 (Deep Cut Road), a distance of 860.70 feet to a R.R. spike set and the PLACE OF BEGINNING for the tract of land herein described;

thence continuing S.89°30'E. along the centerline of County Road 228, a distance of 63.98 feet to a R.R. spike set;

thence S.00°17'52"W. a distance of 375.71 feet to an iron pin set, passing thru an iron pin set for reference at 30.00 feet in the South right-of-way line of County Road 228;

thence S.89°30'E., parallel to the centerline of County Road 228, a distance of 126.00 feet to an iron pin set;

thence N.00°17'52"E. a distance of 375.71 feet to a R.R. spike set, passing thru an iron pin set for reference at 345.71 feet in the South right-of-way line of County Road 228;

thence S.89°30'E. along the centerline of County Road 228, a distance of 834.52 feet to a R.R. spike set;

thence S.00°29'W., parallel to the East line of the Northwest Fractional Quarter of Section 19, Logan Township, a distance of 1,338.20 feet to an iron pin set in the East - West Half Section line of said Section;

thence S.00°17'52"W. a distance of 1,322.99 feet to an iron pin set in the center of the bottom of an obliterated wood corner post;

thence N.89°53'52"W., parallel to the East - West Half Section line of Section 19, Logan Township, a distance of 1,020.17 feet to an iron pin set;

thence N.00°17.52"E. a distance of 2,668.28 feet to a R.R. spike in the centerline of County Road 228, passing thru a wood corner post at 1,322.99 feet in the East - West Half Section line of Section 19, Logan Township, said R.R. spike was the true PLACE OF BEGINNING.

Containing in all 61.45 acres of which 0.62 acre has been dedicated for highway purposes, 30.46 acre being located in the Northwest Fractional Quarter and 30.98 acre being located in the Southwest Fractional Quarter of Section 19. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous Deed reference: Volume 195, page 358. This plat is recorded in Survey Book "H", page 243, in the Auglaize County Engineer's Office.


ATTEST: John W. Jauert; Professional Surveyor No. 6920

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

Signature by a (representative of the) County Commissioner(s)
denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____



Client Joe Mack
County Auglaize Twp. Logan Sec. 19
Drawn by _____ Scale _____ Drwg. No. 88-362-A
Checked by _____ Date May 15th, 1988
Sheet 2 of 2 H-244 (T 4 S; R 5 E)