


LOCATION PLAN SECTION 33



DUCHOUQUET TOWNSHIP
T-4-S, R-6-E, AUGLAIZE
COUNTY, OHIO

LEGEND

- IRON PIN SET
- △ R.R. SPIKE SET
- P.K. NAIL FOUND
- ⬢ STONE FOUND
- MONUMENT BOX




ATTEST: *John W. Jauert*
JOHN W. JAUBERT
PROFESSIONAL SURVEYOR
NR 6920

N.E. CORNER, N.E. 1/4,
SECTION 33, T-4-S,
R-6-E, AUGLAIZE COUNTY.

THIS PLAT IS RECORDED IN SURVEY BOOK H, PAGE 253
IN THE AUGLAIZE COUNTY ENGINEER'S OFFICE.

Jauert
ASSOCIATES



Surveying
AND LAND CONSULTING

RT. 3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

Client EUGENE MYERS
County AUGLAIZE Township DUCHOUQUET
Section 33N T. 4 S., R. 6 E. Drwg. No. 86-165-RB
Drawn By JOHN JAUBERT Date MAY 23 1988
Scale 1"=300' Sheet 1 of 2

CORRECTIVE SURVEYOR'S DESCRIPTION



The following described tract of land is part of the Northeast Quarter of Section 33, Town 4 South, Range 6 East, Duchouquet Township, Auglaize County, Ohio, and is more particularly described as follows:

The PLACE OF BEGINNING is at the Section Stone at the Northwest corner of the Northeast Quarter of Section 33, Duchouquet Township;

thence S89°04'04"E along the North line of the Northeast Quarter of Section 33, Duchouquet Township and the Auglaize-Allen County Line, a distance of 2,648.17 feet to a monument box in the centerline of Township Road 161 (Hauss Road), said monument box being the Northeast corner of the Northeast Quarter of Section 33, Duchouquet Township;

thence S01°04'30"W along the centerline of Township Road 161 (Hauss Road), a distance of 456.32 feet to a R.R. spike;

thence N88°25'30"W a distance of 264.00 feet to a point;

thence S01°04'30"W, parallel to the centerline of Township Road 161, a distance of 165.00 feet to a point;

thence N88°25'30"W a distance of 353.21 feet to an iron pin;

thence S01°04'04"W a distance of 651.38 feet to a R.R. spike in the centerline of County Road 208 (National Road);

thence S90°00'W along the centerline of County Road 208, a distance of 1,703.50 feet to a R.R. spike;

thence N01°10'E a distance of 264.00 feet to an iron pin;

thence S90°00'W on a line parallel to the centerline of County Road 208, a distance of 165.00 feet to an iron pin;

thence N01°10'E along the North - South half Section line of Section 33, Duchouquet Township, a distance of 1,034.87 feet to a Section Stone at the Northwest corner of the Northeast Quarter of Section 33, Duchouquet Township, said Section Stone was the true PLACE OF BEGINNING.

Containing in all 65.573 acres of which 1.186 acres has been dedicated for highway purposes. The above tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume _____, page _____, in the Auglaize County Recorder's Office. This plat is recorded in Survey Book H, page 253 in the Auglaize County Engineer's Office.



ATTEST:

John W. Jauert
John W. Jauert
Professional Survey No. 6920

Jauert
ASSOCIATES

Surveying
AND LAND CONSULTING

RT.3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

Client Eugene Myers
County Auglaize Township Duchouquet
Section 33 T. 4 S., R. 6 E. Drwg. No. _____
Drawn By _____ Date _____
Scale _____ Sheet _____ of _____

H-254