


LOCATION PLAN


SECTION 20



DUCHOUQUET TOWNSHIP,
T-5-S, R-6-E, AUGLAIZE
COUNTY, OHIO.


LEGEND

- IRON PIN SET
- △ R.R. SPIKE SET
- MONUMENT BOX



SCALE

N.E. CORNER,
N.E. 1/4, SEC. 20



ATTEST:

JOHN W. JAUERT
PROFESSIONAL
SURVEYOR NO. 6920



S. LINE, N. 1/2, N.E. 1/4,
SECTION 20

EXISTING FENCE (14'±)

THIS PLAT IS RECORDED IN
SURVEY BOOK "H", PAGE 327,
IN THE AUGLAIZE COUNTY
ENGINEER'S OFFICE.

COUNTY ROAD 166
(INFIRMARY ROAD)

Jauert
ASSOCIATES

Surveying
AND LAND CONSULTING

RT. 3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

Client GEORGE MILLER
County AUGLAIZE Township DUCHOUQUET
Section 20 T. 5 S., R. 6 E. Drwg. No. 88-407
Drawn By J. JAUERT Date OCT. 15, 1988
Scale SHOWN Sheet 1 of 1



SURVEYOR'S DESCRIPTION FOR PARCEL "A"

The following described tract of land is part of the Northeast Quarter of the Northeast Quarter of Section 20, Town 5 South, Range 6 East, Duchouquet Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box over the stone at the Northeast corner of the Northeast Quarter of Section 20, Duchouquet Township, said monument box being at the intersection of the centerlines of Township Road 170 (Linzee Road) and County Road 151 (Wapakoneta - Cridersville Road);

thence S.00°56'51"E. along the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 1,120.59 feet to a R.R. spike set which is the PLACE OF BEGINNING for the tract of land herein described;

thence continuing S.00°56'51"E. along the above described line, a distance of 197.76 feet to a R.R. spike set;

thence S.88°29'54"W. a distance of 330.41 feet to an iron pin set, passing thru an iron pin set for reference at 25.00 feet in the West right-of-way line of County Road 151;


thence N.00°56'51"W., parallel to the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 197.76 feet to an iron pin;

thence N.88°29'54"E. a distance of 330.41 feet to a R.R. spike, passing thru an iron pin set for reference at 305.41 feet in the West right-of-way line of County Road 151, said R.R. spike was the true PLACE OF BEGINNING.


Containing in all 1.50 acre of which 0.11 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume 146, page 455. This plat is recorded in Survey Book "H", page _____, in the Auglaize County Engineer's Office.



ATTEST:


John W. Jauert
Professional Surveyor No. 6920

Jauert
ASSOCIATES




Surveying
AND LAND CONSULTING

RT. 3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

H-328

Client George Miller
County Auglaize Township Duchouquet
Section 20 T. 5 S., R. 6 E. Drwg. No. 88-407
Drawn By _____ Date 10/1/88
Scale _____ Sheet 2 of 5



SURVEYOR'S DESCRIPTION FOR PARCEL "B"

The following described tract of land is part of the Northeast Quarter of the Northeast Quarter of Section 20, Town 5 South, Range 6 East, Duchouquet Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box over the stone at the Northeast corner of the Northeast Quarter of Section 20, Duchouquet Township, said monument box being at the intersection of the centerlines of Township Road 170 (Linzee Road) and County Road 151 (Wapakoneta - Cridersville Road);

thence S.00°56'51"E. along the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 527.30 feet to a R.R. spike set which is the PLACE OF BEGINNING for the tract of land herein described;

thence continuing S.00°56'51"E. along the above described line, a distance of 593.29 feet to a R.R. spike set;

thence S.88°29'54"W. a distance of 330.41 feet to an iron pin set, passing thru an iron pin set for reference at 25.00 feet in the West right-of-way line of County Road 151;


thence N.00°56'51"W., parallel to the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 539.29 feet to an iron pin set;

thence N.88°29'54"E. a distance of 330.41 feet to a R.R. spike, passing thru an iron pin set for reference at 305.41 feet in the West right-of-way line of County Road 151, said R.R. spike was the true PLACE OF BEGINNING.


Containing in all 4.50 acre of which 0.34 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume 146, page 455. This plat is recorded in Survey Book "H", page 327, in the Auglaize County Engineer's office.



ATTEST:


John W. Jauert,
Professional Surveyor No. 6920

Jauert
ASSOCIATES




Surveying
AND LAND CONSULTING

RT.3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

H 329

Client George Miller
County Auglaize Township Duchouquet
Section 20 T. 5 S., R. 6 E. Drwg. No. 88-407
Drawn By _____ Date 10/1/88
Scale _____ Sheet 3 of 5

Jauert
ASSOCIATES



Surveying

AND LAND CONSULTING

RT.3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

Client: GEORGE MILLER

COUNTY AUGLAIZE TOWNSHIP DUCHOUQUET

SECTION 20 T. 5 S., R. 6 E. DRWG. No. 88-407

DRAWN BY _____ DATE REV. 3-11-90

CHECKED BY _____ SHEET 4 OF 5

SURVEYOR'S DESCRIPTION FOR PARCEL "C"

The following described tract of land is part of the Northeast Quarter of the Northeast Quarter of Section 20, Town 5 South, Range 6 East, Duchouquet Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box over the stone at the Northeast corner of the Northeast Quarter of Section 20, Duchouquet Township, said monument box being at the intersection of the centerlines of Township Road 170 (Linzee Road) and County Road 151 (Wapakoneta - Cridersville Road);

thence S. $00^{\circ}56'51''$ E. along the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 263.65 feet to a R.R. spike set which is the PLACE OF BEGINNING for the tract of land herein described;

thence continuing S. $00^{\circ}56'51''$ E. along the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 263.65 feet to a R.R. spike set;


thence S. $88^{\circ}29'54''$ W. a distance of 330.41 feet to an iron pin set, passing thru an iron pin set for reference at 25.00 feet in the West right-of-way line of County Road 151;

thence N. $00^{\circ}56'51''$ W., parallel to the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 263.65 feet to an iron pin set;

thence N. $88^{\circ}29'54''$ E. a distance of 330.41 feet to a R.R. spike, passing thru an iron pin set for reference at 305.41 feet in the West right-of-way line of County Road 151, said R.R. spike was the true PLACE OF BEGINNING.

Containing in all 2.00 acre of which 0.15 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume 146, page 455. This plat is recorded in Survey Book "H", page 327, in the Auglaize County Engineer's Office.

ATTEST;


John W. Jauert
Professional Surveyor No. 6920



H-330



SURVEYOR'S DESCRIPTION FOR PARCEL "D"

The following described tract of land is part of the Northeast Quarter of the Northeast Quarter of Section 20, Town 5 South, Range 6 East, Duchouquet Township, Auglaize County, Ohio and is more particularly described as follows:

The PLACE OF BEGINNING is at a monument box over the stone at the Northeast corner of the Northeast Quarter of Section 20, Duchouquet Township, said monument box being at the intersection of the centerlines of Township Road 170 (Linzee Road) and County Road 151 (Wapakoneta - Cridersville Road);

thence S.00°56'51"E. along the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 263.65 feet to a R.R. spike set;

thence S.88°29'54"W. a distance of 330.41 feet to an iron pin set, passing thru an iron pin set for reference at 25.00 feet in the West right-of-way line of County Road 151;


thence N.00°56'51"W., parallel to the centerline of County Road 151 and the East line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 263.65 feet to a R.R. spike set, passing thru an iron pin set for reference at 243.65 feet in the South right-of-way line of Township Road 170;

thence N.88°29'54"E. along the centerline of Township Road 170 and the North line of the Northeast Quarter of Section 20, Duchouquet Township, a distance of 330.41 feet to a monument box, which was the true PLACE OF BEGINNING.


Containing in all 2.00 acre of which 0.29 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume 146, page 455. This plat is recorded in Survey Book "H", page _____, in the Auglaize County Engineer's Office.



ATTEST:


John W. Jauert
Professional Surveyor No. 6920

Jauert
ASSOCIATES



Surveying
AND LAND CONSULTING

RT. 3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

H-331

Client George Miller

County Auglaize Township Duchouquet

Section 20 T. 5 S., R. 6 E. Drwg. No. 88-407

Drawn By _____ Date 10/1/88

Scale _____ Sheet 5 of 5