



The following described tract of land is part of the Northwest Quarter of the Southeast Quarter of Section 8, Town 5 South, Range 4 East, Noble Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at an iron pin found at the center of Section 8, Noble Township, and in the centerline of Township Road 25, (Fike Road);
thence S.00°02'37"E. along the West line of the Southeast Quarter of Section 8, Noble Township and the centerline of Township Road 25, a distance of 664.25 feet to a R.R. spike set, which is the PLACE OF BEGINNING for the tract of land herein described;
thence N.89°17'38"E. a distance of 251.36 feet to an iron pin set;
thence S.00°02'37"E., parallel to the West line of the Southeast Quarter of Section 8, Noble Township, a distance of 250.00 feet to an iron pin set;
thence S.89°17'36"W. a distance of 251.36 feet to an iron pin set;
thence N.00°02'37"W. along the West line of the Southeast Quarter of Section 8, Noble Township and the centerline, extended, of Township Road 25, a distance of 250.00 feet to a R.R. spike which was the true PLACE OF BEGINNING.

Containing in all 1.44 acre and being subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume 213, page 566. This plat is recorded in Survey Book "H", page 332, in the Auglaize County Engineer's Office.



ATTEST: John W. Jauert
John W. Jauert
Professional Surveyor No. 6920

Jauert
ASSOCIATES

Surveying
AND LAND CONSULTING

RT.3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

Client Tom Menchofer
County Auglaize Township Noble
Section 8 T. 5 S., R. 4 E. Drwg. No. 88-409
Drawn By J. Jauert Date 10/10/88
Scale 1" = 100' Sheet 1 of 1

H-332