

## DESCRIPTION FARCEL NO. 1

Being a parcel of land situate in the North half of the Northeast Guarter of Section 12, T-7-S, R-4-E, German Township, Auglaize County, Ohio and more particularly described as follows:

at a monument box found over a stone at the BEGINNING said Northeast Quarter of said Section 12; thence corner of S 02°00'00' W (assumed bearing) with the east line of Northeast Quarter (also the centerline of East Shelby Road - T.R. 71), 1327,30 feet to a PK nail set at the southeast conner of the north half of said Northeast Quarter; thence N 88°16'42" W with the south line of said north half of said Northeast Guarter, 1997.23 feet to a ten (10) inch wood corner bost found at southwest corner of the east half of the morthwest quarter said Northeast Guarter of said Section 12; thence N 00°17'09" W with the west line of said east half, 1327.39 feet to a PK nail set at the northwest corner of said east half; thence S 88°15'55" E with the north line of said Northeast Quarter of said Section 12 (also the centerline of Lock Two Road - C.R. 70), 945.73 feet to a PK nail set; thence S 00°05'50" W, to a six (6) inch wood corner bost found; thence S 88°52'00" E, 580.04 feet to a six (6) inch wood corner post found; thence N 00°00'35" W, 375.04 feet to a PK nail set on the north line of said Northeast Quarter (also the centerline of Lock Two Road - C.R. 70); thence S 88°16'55" E with said north line and centerline, 478.64 feet to the PLACE OF BEGINNING containing 55.898 acres more or less and subject to all highways and other legal easements of record.

## DESCRIPTION PARCEL NO. 2

Being a parcel of land situate in the North half of the Northeast Quarter of Section 12, T-7-5, R-4-E, German Township, Auglaize County, Ohio and more particularly described as follows:

Commencing at a monument box found over a stone at the northeast corner of said Northeast Quarter of said Section 12; thence N 88°16'55" W the north line of said Northeast Quarter (also the centerline of Lock Two Road - C.R. 70), 478.64 feet to a PK nail set and the PLACE OF BEGINNING thence continuing N 88°16'55" W the said north line and centerline, 579.48 feet to a PK nail set; thence S  $00^{\circ}05'50"$  W, 380.94 feet to a six (6) inch wood corner bost found; thence S  $88^{\circ}52'02"$  E, 580.04 feet to a six (6) inch wood corner post found; thence N  $00^{\circ}00'35"$  W, 375.04 feet to the PLACE OF BEGINNING containing 5.029 acres more or less and subject to all highways and other legal easements of record.

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed:		Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.  Signed:  Date
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:		Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date
KUCK AND MORRISEY, INC.  CONSULTING ENGINEERS & SURVEYORS  2807 CHAPEL HILL DRIVE  LIMA, OHIO 45805 - 228-1735	Client Kermit Brandt Estate Voltes Joyce Hein/ County Augloize Twp. German Sec. 12  Drawn by RDM Scale "= 330 Drwg. No Checked by rdm Date 11-9-88  Sheet 2 of 2 H-573 (T-7-S: R-4-E)	