

LEGEND

- "A" = FOUND O.D.O.T. IRON BAR SET OVER STONE
- "B" = R.R. SPIKE FOUND AT N.W. CORNER OF S.W. 1/4 OF THE N.W. 1/4, SEC. 21
- "C" = MON. BOX. FD. @ N. 1/4 POST, SEC. 21
- "D" = STONE FOUND @ CENTER SEC. 21
- "E" = MINE SPIKE SET & PUNCHED
- "F" = 5/8" IRON BAR SET

SURVEYED BY:

Michael L. Weadock
MICHAEL L. WEADOCK
PROF. SURVEYOR #6199

SURVEY OF PART OF THE S.W. 1/4 OF THE N.W. 1/4
OF SECTION 21, TOWN 5 SOUTH, RANGE 4 EAST,
(NOBLE TWP.), AUGLAIZE COUNTY, OHIO
JAN. 1987
SCALE: 1"=100'

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

MICHAEL L. WEADOCK
PROF. SURVEYOR N° 6199
ST. MARYS, OHIO

Client DAVID LIETTE
County AUGLAIZE Twp. NOBLE Sec. 21
Drawn by S.C.O. Scale 1"=100' Drwg. No. 1
Checked by M.L.W. Date 1-20-87
Sheet 1 of 2 14-664 (T 5 S; R 4 E)

LIETTE SURVEY DESCRIPTION



Scale:

Being a parcel of land situated in the southwest quarter of the northwest quarter of Section 21, Town 5 South, Range 4 East, (Noble Township), Auglaize County, Ohio, and being more particularly described as follows:

Commencing for reference at an iron pin found over the corner stone at the west quarter post of said Section 21,

Thence, North 0° 14' 40" East, along the west line of the northwest quarter of said Section 21 and the centerline of State Route #116, a distance of one thousand one hundred thirty-one and 50/100 (1131.50) feet to a mine spike set; said point being the place of beginning for the parcel to be conveyed by this instrument;

Thence, continuing, North 0° 14' 40" East, along the last described line a distance of one hundred ninety-seven and 07/100 (197.07) feet to a railroad spike found; said point being the northwest corner of the southwest quarter of the northwest quarter of said Section 21;

Thence, South 89° 36' 06" East, along the north line of the southwest quarter of the northwest quarter of said Section 21, a distance of four hundred forty-two and 08/100 (442.08) feet to a 5/8" iron bar set;

Thence, South 0° 14' 40" West, parallel with the west line of the northwest quarter of said Section 21, a distance of one hundred ninety-seven and 07/100 (197.07) feet to a 5/8" iron bar set;

Thence, North 89° 36' 06" West, parallel with the north line of the southwest quarter of the northwest quarter of said Section 21, a distance of four hundred forty-two and 08/100 (442.08) feet to the place of beginning.

Containing 2.000 acres of land more or less of which 0.1357 acres is in road right-of-way.


Subject to all easements and rights-of-way of record.

The west line of the northwest quarter of Section 21 was assumed to bear North 0° 14' 40" East. All other bearings were calculated from angles turned.

Reference is made to a boundary survey of this area by Michael L. Weadock, Professional Surveyor No. 6199, dated January, 1987, on file in the County Engineer's Office.

Surveyed by:

Michael L. Weadock
Michael L. Weadock
Professional Surveyor No. 6199



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

MICHAEL L. WEADOCK
PROF. SURVEYOR N°6199
ST. MARYS, OHIO

Client DAVID LIETTE
County AUGLAIZE Twp. NOBLE Sec. 21
Drawn by — Scale — Drwg. No. —
Checked by M.L.W. Date 1-20-87
Sheet 2 of 2 H-665 (T 5 S; R 4 E)