

$$A'' = \frac{\text{STONE}}{\text{SEC. 30}} \text{ AT S.W. COR. } 2 \frac{1}{4} \text{ N } 3 \frac{1}{4} \text{ E } 4$$

"B" = FROM PIPE FLD FROM SURVEYS BY
TOM STEINKE, REG.

[illegible]

W. LINE ~ N.W. $\frac{1}{4}$ ~ SEC. 30

RANDOLPH COLSON
VOL 263, PG. 342

1.100
ACRES

DAVID OVERMAN
VOL. 259, PG. 307

THIS BEARING ACCEPTED
ALL OTHER CALCULATED
-FROM ANGLES TURNED
N. 88° 52'
E. 37° 12'

LOCATION
SKETCH

SECTION 30

SECTION 30

ART DEITSCH
O. R. 21, PG. 394

SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR
N^o 5372



SAINTIGNON SURVEY

PART OF THE N.W. $\frac{1}{4}$ ~ N.W. $\frac{1}{4}$ ~ SECTION 30, TOWN
5 SOUTH, RANGE 4 EAST (NOBLE TOWNSHIP),
AUGLAIZE COUNTY, OHIO.

SEPT. 13, 1986

SCALE 1" = 100'

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____
for political S. D. of: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

September 13, 1986

SAINTIGNON SURVEY DESCRIPTION

Being a parcel of and situated in Noble Township, Auglaize County, Ohio, in the northwest quarter of the northwest quarter of Section 30, Township 5 South, Range 2 East. Being more particularly described as follows:

Commencing for reference at the corner stone at the southwest corner of the northwest quarter of the northwest quarter of said Section 30-

Thence, south $88^{\circ}52'22''$ east, along the south line of said northwest quarter of the northwest quarter of Section 30, a distance of one hundred fifty-four and $25/100$ (154.25) feet to the southeast corner of a four acre tract of land conveyed to Randolph and Janice Colson by deed recorded in Deed Volume 263, page 342. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing south $88^{\circ}52'22''$ east, along the last described line, a distance of one hundred twenty-nine and $64/100$ (129.64) feet to a $5/8$ inch iron bar-

Thence, north $05^{\circ}07'20''$ east, a distance of three hundred forty-four and $65/100$ (344.65) feet to a $5/8$ inch iron bar-

Thence, north $88^{\circ}52'22''$ west, a distance of thirty-four and $86/100$ (34.86) feet to an iron pipe at the southeast corner of a one acre tract of land conveyed to David L. Overman by deed recorded in Deed Volume 259, page 307-

Thence, north $50^{\circ}45'15''$ west, along said Overman's south line, a distance of one hundred fourteen and $21/100$ (114.21) feet to an iron pipe at the southwest corner thereof-


Thence, south $05^{\circ}07'20''$ west, along the afore mentioned Colson's east line, a distance of four hundred fifteen and $32/100$ (415.32) feet to the place of beginning. Said line passing through an iron pipe at four hundred fourteen and $69/100$ (414.69) feet.

Containing 1.100 acre of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated September 13, 1986, on file in the County Engineer's Office.

Surveyed by


Gordon L. Geeslin
Registered Surveyor 5372



101 SOUTH LEBLOND STREET

CELINA, OHIO 45822

H 671