

AUGLAIZE
County

MON. BOX
@ N. 1/4 POST
SEC. 30

RR. SPK
FOUND

RR. SPK
FD

MINE SPK
SET

MINE SPK
SET

RR. SPK
FOUND

MON. BOX
@ CENTER
SEC. 30

W. LINE ~ N.E. 1/4 ~ SEC. 30 & KOENIG ROAD

N. LINE ~ S. 1/2 ~ S. 1/2 ~ N.W. 1/4 ~ N.E. 1/4 ~ SEC. 30

DOUGLAS WEAVER
O.R. VOL. 19, PG. 908

TRACT A-3
2,000 ACRES

S. 89° 59' 49" W. ~ 378.78'


N. 89° 40' 23" E. ~ 378.78'

TRACT A-4
2,000 ACRES

S. 89° 40' 23" W. ~ 378.78'

SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR
No 5372

LOCATION
SKETCH



SECTION 30



CARPENTER SURVEY
PART OF THE W. 1/2 ~ N.E. 1/4 ~ SECTION 30,
TOWN 5 SOUTH, RANGE 4 EAST (NOBLE TWP.),
AUGLAIZE COUNTY, OHIO.
APRIL 13, 1987

SCALE 1" = 200'

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

GORDON L. GEESLIN
LAND SURVEYOR
CELINA, OHIO

Client RANDY CARPENTER
County AUGLAIZE Twp. NOBLE Sec. 30
Drawn by G.L.G. Scale 1"=200 Drwg. No. _____
Checked by _____ Date APRIL 13, 1987
Sheet 1 of 1 H-674 (T 5 S; R 4 E)

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

April 13, 1987

CARPENTER SURVEY DESCRIPTION (TRACT A-4)

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the west half of the northeast quarter of Section 30, Town 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at an iron bar in the monument box at the center of said Section 30-

Thence, north 00°01'37" west, along the west line of the northeast quarter of said Section 30 and the centerline of Koenig road, a distance of six hundred sixty-nine and 10/100 (669.10) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing north 00°01'37" west, along the last described line, a distance of two hundred thirty (230.00) feet to a mine spike-

Thence, north 89°40'23" east, a distance of three hundred seventy-eight and 78/100 (378.78) feet to a 5/8 inch iron bar-

Thence, south 00°01'37" east, a distance of two hundred thirty (230.00) feet to a 5/8 inch iron bar-

Thence, south 89°40'23" west, a distance of three hundred seventy-eight and 78/100 (378.78) feet to the place of beginning.

Containing 2.000 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated April 13, 1987, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin
Gordon L. Geeslin
Registered Surveyor 5372



101 SOUTH LEBLOND STREET

CELINA, OHIO 45822

H-675

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

April 13, 1987

CARPENTER SURVEY DESCRIPTION (TRACT A-3)

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the west half of the northeast quarter of Section 30, Town 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at an iron bar in the monument box at the center of said Section 30-

Thence, north 00°01'37" west, along the west line of the northeast quarter of said Section 30 and the centerline of Koenig road, a distance of one thousand two hundred one and 91/100 (1201.91) feet to a mine spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing north 00°01' 37" west, along the last described line, a distance of two hundred thirty (230.00) feet to a railroad spike-

Thence, north 89°59'49" east, a distance of three hundred seventy-eight and 78/100 (378.78) feet to a 5/8 inch iron bar-

Thence, south 00°01'37" east, a distance of two hundred thirty (230.00) feet to a 5/8 inch iron bar-

Thence, south 89°59'49" west, a distance of three hundred seventy-eight and 78/100 (378.78) feet to the place of beginning.

Containing 2.000 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated April 13, 1987, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin

Registered Surveyor 5372



101 SOUTH LEBLOND STREET

CELINA, OHIO 45822

H-676