

A circular professional seal for Richard D. Morrisey, a Registered Professional Surveyor in the State of Ohio. The seal features a double-lined circular border. Between the lines, the words "STATE OF OHIO" are written in an arc at the top, and "REGISTERED PROFESSIONAL SURVEYOR" is written in an arc at the bottom. Two five-pointed stars are positioned on the right side, separating the top and bottom text. In the center of the seal, the name "RICHARD D. MORRISEY" is printed in a bold, sans-serif font. Below the name, the registration number "6470" is printed in a smaller font.

NW Corner SW $\frac{1}{4}$
 Section 3, Pusheta Twp.
 S 89°.25' 21"E, 1678.44'
 2.40'


Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____ Date _____

for political S. D. of: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____


 J. Edgar Hoover
 U.S. 6470

Client John Kemper
County Avulaine Twp. Pusheta Sec. 3
Drawn by EDM Scale _____
Checked by rdm Date 11/24/86
Sheet 1 of 2 (T-C-S; R-C-E)
H-679

DESCRIPTION FOR
SIXTY FIVE FOOT
EASEMENT FOR SANITARY
SEWAGE LEACHING FIELD

Being a parcel of land situate in the north one-third of the Southwest quarter of Section 3, T-6-S, R-6-E, Pusheta Township, Auglaize County, Ohio and more particularly described as follows:


Commencing at a monument box over a stone found at the northwest corner of said Southwest quarter of said Section 3; thence S 89°25'21" E with the east-west half section line of said Section 3 (passing through an iron pipe found at 740.50 feet), 1678.44 feet to a 5/8" rebar found; thence S 00°00'00" W, 882.40 feet to a 5/8" rebar found on the south line of said north one-third of said Southwest quarter; thence S 89°25'30" E with said south line, 694.61 feet to the PLACE OF BEGINNING thence N 00°34'30" E, 221.23 feet to a point; thence S 89°25'30" E, 65.00 feet to a 5/8" rebar found; thence S 00°34'30" W, 221.23 feet to a 5/8" rebar found on the south line of said north one-third of said Southwest quarter; thence N 89°25'30" W with said south line, 65.00 feet to the PLACE OF BEGINNING containing 0.330 acre more or less.

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____


LS. 6470

Client John Kemper
County Auglaize Twp. Pusheta Sec. 3
Drawn by EDM Scale _____ Drwg. No. _____
Checked by rdm Date 11/24/86
Sheet 2 of 2 H-680 (T-6-S; R-6-E)