
LEGEND

- "A" = FOUND 1" BAR IN MON. BOX
AT W 1/4 POST, SEC. 12
- "B" = FOUND 1" BAR IN MON. BOX
AT S.W. CORNER, SEC. 12
- "C" = IRON PIPE FOUND (SEE JOHNS
SURVEY CONDUCTED BY THOMAS
STEINKE, SEPT. 1977 ON FILE
AT THE AUG.CO-ENG. OFFICE
BOOK "C", PAGE 223
- "D" = RAILROAD SPIKE SET & PUNCHED
- "E" = 5/8" IRON BAR SET

SECTION 12LOCATION
SKETCH

SURVEY OF PART OF THE WEST 1/2 OF THE
S.W. 1/4 OF SECTION 12, TOWNSHIP 6 SOUTH, RANGE
4 EAST, (ST. MARYS TWP.), AUGLAIZE CTY., OHIO

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____
for political S. D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

MICHAEL L. WEADOCK
PROF. SURVEYOR #
6199 ~ ST. MARYS, O.

Client DAVID STROH
County AUGLAIZE Twp. ST. MARYS Sec. 12
Drawn by S.C.O. Scale 1" = 100' Drwg. No. 1
Checked by M.L.W. Date 3-24-87
Sheet 1 of 2 14-758 (T. 6 S.; R. 4 E.)

STROH SURVEY DESCRIPTION



Scale: _____

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the west half of the southwest quarter of Section 12, Town 6 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at an iron bar at the west quarter post of said Section 12,

Thence, South, along the west line of the southwest quarter of said Section 12, said line also being the centerline of Plattner Road, a distance of thirty and 00/100 (30.00) feet to a railroad spike. Said point being the place of beginning for the parcel to be conveyed by this instrument;

Thence, continuing, South, along the last described line a distance of two hundred ten and 00/100 (210.00) feet to a railroad spike;

Thence, North $89^{\circ} 22' 50''$ East, a distance of four hundred fourteen and 86/100 (414.86) feet to a 5/8" iron bar;

Thence, North, a distance of two hundred ten and 00/100 (210.00) feet to a 5/8" iron bar;

Thence, South $89^{\circ} 22' 50''$ West, a distance of four hundred fourteen and 86/100 (414.86) feet to the place of beginning.

Containing 2.000 acres of land more or less of which 0.1928 acres is in road right-of-way.

Subject to all easements and rights-of-way of record.


The west line of the southwest quarter of Section 12 was assumed to bear North-South. All other bearings were calculated from angles turned.

Reference is made to a boundary survey of this are by Michael L. Weadock, Professional Surveyor #6199, completed in March, 1987, on file in the County Engineer's Office.

Surveyed by:

Michael L. Weadock

Professional Surveyor #6199



Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____ Date: _____
for political S. D. of: _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date: _____

MICHAEL WEADOCK
PROF. SURVEYOR #6199
ST. MARYS, OHIO

Client DAVID STROH
County AUGLAIZE Twp. ST. MARKS Sec. 12
Drawn by N/A Scale N/A Drwg. No. N/A
Checked by MLW Date 3-26-87
Sheet 2 of 2 H-759 (T 6 S; R 4 E)